



THE GUIDE OF

QVD API Integration

QVD DOCUMENTATION

<documentation@theqvd.com>

Other contributors: *Francisco Trapero*

July 11, 2017

Contents

1	Paths	1
2	Types	1
3	/api	2
3.1	Login	3
3.2	ACLs	3
3.2.1	acl_get_list	3
3.2.1.1	Description	3
3.2.1.2	ACLs	3
3.2.1.3	Parameters	3
3.2.1.4	Examples	4
3.2.2	get_acls_in_roles	4
3.2.2.1	Description	4
3.2.2.2	ACLs	4
3.2.2.3	Parameters	4
3.2.2.4	Examples	5
3.2.3	get_acls_in_admins	5
3.2.3.1	Description	5
3.2.3.2	ACLs	5
3.2.3.3	Parameters	5
3.2.3.4	Examples	6
3.2.4	acl_tiny_list	6
3.2.4.1	Description	6
3.2.4.2	ACLs	6
3.2.4.3	Parameters	6
3.2.4.4	Examples	6
3.2.5	number_of_acls_in_role	7
3.2.5.1	Description	7
3.2.5.2	ACLs	7
3.2.5.3	Parameters	7
3.2.5.4	Examples	7
3.2.6	number_of_acls_in_admin	7
3.2.6.1	Description	7
3.2.6.2	ACLs	7
3.2.6.3	Parameters	8
3.2.6.4	Examples	8

3.3	Roles	8
3.3.1	role_get_list	8
3.3.1.1	Description	8
3.3.1.2	ACLs	8
3.3.1.3	Parameters	8
3.3.1.4	Examples	9
3.3.2	role_get_details	10
3.3.2.1	Description	10
3.3.2.2	ACLs	10
3.3.2.3	Parameters	10
3.3.2.4	Examples	10
3.3.3	role_tiny_list	11
3.3.3.1	Description	11
3.3.3.2	ACLs	11
3.3.3.3	Parameters	11
3.3.3.4	Examples	11
3.3.4	role_all_ids	12
3.3.4.1	Description	12
3.3.4.2	ACLs	12
3.3.4.3	Parameters	12
3.3.4.4	Examples	13
3.3.5	role_create	13
3.3.5.1	Description	13
3.3.5.2	ACLs	13
3.3.5.3	Parameters	13
3.3.5.4	Examples	13
3.3.6	role_update	14
3.3.6.1	Description	14
3.3.6.2	ACLs	14
3.3.6.3	Parameters	14
3.3.6.4	Examples	14
3.3.7	role_delete	14
3.3.7.1	Description	14
3.3.7.2	ACLs	15
3.3.7.3	Parameters	15
3.3.7.4	Examples	15
3.4	Tenants	15
3.4.1	tenant_get_list	15
3.4.1.1	Description	15

3.4.1.2	ACLs	15
3.4.1.3	Parameters	15
3.4.1.4	Examples	16
3.4.2	tenant_get_details	17
3.4.2.1	Description	17
3.4.2.2	ACLs	17
3.4.2.3	Parameters	17
3.4.2.4	Examples	18
3.4.3	tenant_tiny_list	18
3.4.3.1	Description	18
3.4.3.2	ACLs	18
3.4.3.3	Parameters	18
3.4.3.4	Examples	19
3.4.4	tenant_all_ids	19
3.4.4.1	Description	19
3.4.4.2	ACLs	19
3.4.4.3	Parameters	19
3.4.4.4	Examples	20
3.4.5	tenant_create	20
3.4.5.1	Description	20
3.4.5.2	ACLs	20
3.4.5.3	Parameters	20
3.4.5.4	Examples	21
3.4.6	tenant_update	21
3.4.6.1	Description	21
3.4.6.2	ACLs	21
3.4.6.3	Parameters	21
3.4.6.4	Examples	21
3.4.7	tenant_delete	22
3.4.7.1	Description	22
3.4.7.2	ACLs	22
3.4.7.3	Parameters	22
3.4.7.4	Examples	22
3.4.8	mytenant_update	22
3.4.8.1	Description	22
3.4.8.2	ACLs	22
3.4.8.3	Parameters	22
3.4.8.4	Examples	23
3.5	Administrators	23

3.5.1	current_admin_setup	23
3.5.1.1	Description	23
3.5.1.2	ACLs	23
3.5.1.3	Parameters	23
3.5.1.4	Examples	23
3.5.2	administrator_get_list	24
3.5.2.1	Description	24
3.5.2.2	ACLs	24
3.5.2.3	Parameters	24
3.5.2.4	Examples	25
3.5.3	administrator_get_details	26
3.5.3.1	Description	26
3.5.3.2	ACLs	26
3.5.3.3	Parameters	26
3.5.3.4	Examples	26
3.5.4	administrator_tiny_list	27
3.5.4.1	Description	27
3.5.4.2	ACLs	27
3.5.4.3	Parameters	27
3.5.4.4	Examples	27
3.5.5	administrator_all_ids	28
3.5.5.1	Description	28
3.5.5.2	ACLs	28
3.5.5.3	Parameters	28
3.5.5.4	Examples	29
3.5.6	administrator_create	29
3.5.6.1	Description	29
3.5.6.2	ACLs	29
3.5.6.3	Parameters	29
3.5.6.4	Examples	29
3.5.7	administrator_update	30
3.5.7.1	Description	30
3.5.7.2	ACLs	30
3.5.7.3	Parameters	30
3.5.7.4	Examples	30
3.5.8	administrator_delete	31
3.5.8.1	Description	31
3.5.8.2	ACLs	31
3.5.8.3	Parameters	31

3.5.8.4	Examples	31
3.5.9	myadmin_update	31
3.5.9.1	Description	31
3.5.9.2	ACLs	31
3.5.9.3	Parameters	31
3.5.9.4	Examples	31
3.6	Users	32
3.6.1	user_get_list	32
3.6.1.1	Description	32
3.6.1.2	ACLs	32
3.6.1.3	Channels	32
3.6.1.4	Parameters	32
3.6.1.5	Examples	33
3.6.2	user_get_details	34
3.6.2.1	Description	34
3.6.2.2	ACLs	34
3.6.2.3	Channels	34
3.6.2.4	Parameters	34
3.6.2.5	Examples	35
3.6.3	user_tiny_list	35
3.6.3.1	Description	35
3.6.3.2	ACLs	35
3.6.3.3	Parameters	35
3.6.3.4	Examples	36
3.6.4	user_all_ids	36
3.6.4.1	Description	36
3.6.4.2	ACLs	36
3.6.4.3	Parameters	36
3.6.4.4	Examples	37
3.6.5	user_get_state	37
3.6.5.1	Description	37
3.6.5.2	ACLs	37
3.6.5.3	Parameters	37
3.6.5.4	Examples	38
3.6.6	user_create	38
3.6.6.1	Description	38
3.6.6.2	ACLs	38
3.6.6.3	Parameters	38
3.6.6.4	Examples	38

3.6.7	user_update	39
3.6.7.1	Description	39
3.6.7.2	ACLs	39
3.6.7.3	Parameters	39
3.6.7.4	Examples	39
3.6.8	user_delete	40
3.6.8.1	Description	40
3.6.8.2	ACLs	40
3.6.8.3	Parameters	40
3.6.8.4	Examples	40
3.7	Hosts	40
3.7.1	host_get_list	40
3.7.1.1	Description	40
3.7.1.2	ACLs	40
3.7.1.3	Channels	41
3.7.1.4	Parameters	41
3.7.1.5	Examples	41
3.7.2	host_get_details	42
3.7.2.1	Description	42
3.7.2.2	ACLs	42
3.7.2.3	Channels	42
3.7.2.4	Parameters	42
3.7.2.5	Examples	43
3.7.3	host_tiny_list	44
3.7.3.1	Description	44
3.7.3.2	ACLs	44
3.7.3.3	Parameters	44
3.7.3.4	Examples	44
3.7.4	host_all_ids	44
3.7.4.1	Description	44
3.7.4.2	ACLs	45
3.7.4.3	Parameters	45
3.7.4.4	Examples	45
3.7.5	host_get_state	45
3.7.5.1	Description	45
3.7.5.2	ACLs	46
3.7.5.3	Parameters	46
3.7.5.4	Examples	46
3.7.6	host_create	46

3.7.6.1	Description	46
3.7.6.2	ACLs	46
3.7.6.3	Parameters	46
3.7.6.4	Examples	47
3.7.7	host_update	47
3.7.7.1	Description	47
3.7.7.2	ACLs	47
3.7.7.3	Parameters	47
3.7.7.4	Examples	48
3.7.8	host_delete	48
3.7.8.1	Description	48
3.7.8.2	ACLs	48
3.7.8.3	Parameters	48
3.7.8.4	Examples	48
3.8	OSFs	49
3.8.1	osf_get_list	49
3.8.1.1	Description	49
3.8.1.2	ACLs	49
3.8.1.3	Channels	49
3.8.1.4	Parameters	49
3.8.1.5	Examples	50
3.8.2	osf_get_details	51
3.8.2.1	Description	51
3.8.2.2	ACLs	51
3.8.2.3	Channels	51
3.8.2.4	Parameters	51
3.8.2.5	Examples	51
3.8.3	osf_tiny_list	52
3.8.3.1	Description	52
3.8.3.2	ACLs	52
3.8.3.3	Parameters	52
3.8.3.4	Examples	52
3.8.4	osf_all_ids	53
3.8.4.1	Description	53
3.8.4.2	ACLs	53
3.8.4.3	Parameters	53
3.8.4.4	Examples	53
3.8.5	osf_create	54
3.8.5.1	Description	54

3.8.5.2	ACLs	54
3.8.5.3	Parameters	54
3.8.5.4	Examples	54
3.8.6	osf_update	54
3.8.6.1	Description	54
3.8.6.2	ACLs	54
3.8.6.3	Parameters	54
3.8.6.4	Examples	55
3.8.7	osf_delete	55
3.8.7.1	Description	55
3.8.7.2	ACLs	55
3.8.7.3	Parameters	55
3.8.7.4	Examples	55
3.9	Disk Images	56
3.9.1	di_get_list	56
3.9.1.1	Description	56
3.9.1.2	ACLs	56
3.9.1.3	Parameters	56
3.9.1.4	Examples	57
3.9.2	di_get_details	58
3.9.2.1	Description	58
3.9.2.2	ACLs	58
3.9.2.3	Parameters	58
3.9.2.4	Examples	59
3.9.3	di_all_ids	59
3.9.3.1	Description	59
3.9.3.2	ACLs	59
3.9.3.3	Parameters	60
3.9.3.4	Examples	60
3.9.4	di_tiny_list	60
3.9.4.1	Description	60
3.9.4.2	ACLs	61
3.9.4.3	Parameters	61
3.9.4.4	Examples	61
3.9.5	tag_get_list	61
3.9.5.1	Description	61
3.9.5.2	ACLs	62
3.9.5.3	Parameters	62
3.9.5.4	Examples	62

3.9.6	tag_tiny_list	63
3.9.6.1	Description	63
3.9.6.2	ACLs	63
3.9.6.3	Parameters	63
3.9.6.4	Examples	63
3.9.7	di_create	64
3.9.7.1	Description	64
3.9.7.2	ACLs	64
3.9.7.3	Parameters	64
3.9.7.4	Examples	64
3.9.8	di_update	64
3.9.8.1	Description	64
3.9.8.2	ACLs	64
3.9.8.3	Parameters	64
3.9.8.4	Examples	65
3.9.9	di_delete	66
3.9.9.1	Description	66
3.9.9.2	ACLs	66
3.9.9.3	Parameters	66
3.9.9.4	Examples	66
3.9.10	dis_in_staging	66
3.9.10.1	Description	66
3.9.10.2	ACLs	66
3.9.10.3	Parameters	66
3.9.10.4	Examples	67
3.10	Configuration	67
3.10.1	config_get	67
3.10.1.1	Description	67
3.10.1.2	ACLs	67
3.10.1.3	Parameters	67
3.10.1.4	Examples	68
3.10.2	config_ssl	69
3.10.2.1	Description	69
3.10.2.2	ACLs	69
3.10.2.3	Parameters	69
3.10.2.4	Examples	69
3.10.3	config_set	69
3.10.3.1	Description	69
3.10.3.2	ACLs	69

3.10.3.3	Parameters	69
3.10.3.4	Examples	70
3.10.4	config_delete	70
3.10.4.1	Description	70
3.10.4.2	ACLs	70
3.10.4.3	Parameters	70
3.10.4.4	Examples	70
3.10.5	config_wat_get_details	71
3.10.5.1	Description	71
3.10.5.2	ACLs	71
3.10.5.3	Parameters	71
3.10.5.4	Examples	71
3.10.6	config_wat_update	71
3.10.6.1	Description	71
3.10.6.2	ACLs	71
3.10.6.3	Parameters	71
3.10.6.4	Examples	72
3.11	Properties	72
3.11.1	property_get_list	72
3.11.1.1	Description	72
3.11.1.2	ACLs	72
3.11.1.3	Parameters	72
3.11.1.4	Examples	73
3.11.2	property_create	73
3.11.2.1	Description	73
3.11.2.2	ACLs	73
3.11.2.3	Parameters	73
3.11.2.4	Examples	74
3.11.3	property_update	74
3.11.3.1	Description	74
3.11.3.2	ACLs	74
3.11.3.3	Parameters	74
3.11.3.4	Examples	74
3.11.4	property_delete	75
3.11.4.1	Description	75
3.11.4.2	ACLs	75
3.11.4.3	Parameters	75
3.11.4.4	Examples	75
3.11.5	host_get_property_list	75

3.11.5.1	Description	75
3.11.5.2	ACLs	75
3.11.5.3	Parameters	75
3.11.5.4	Examples	76
3.11.6	host_create_property_list	76
3.11.6.1	Description	76
3.11.6.2	ACLs	76
3.11.6.3	Parameters	76
3.11.6.4	Examples	76
3.11.7	host_delete_property_list	77
3.11.7.1	Description	77
3.11.7.2	ACLs	77
3.11.7.3	Parameters	77
3.11.7.4	Examples	77
3.11.8	user_get_property_list	77
3.11.8.1	Description	77
3.11.8.2	ACLs	78
3.11.8.3	Parameters	78
3.11.8.4	Examples	78
3.11.9	user_create_property_list	78
3.11.9.1	Description	78
3.11.9.2	ACLs	78
3.11.9.3	Parameters	78
3.11.9.4	Examples	79
3.11.10	user_delete_property_list	79
3.11.10.1	Description	79
3.11.10.2	ACLs	79
3.11.10.3	Parameters	79
3.11.10.4	Examples	79
3.11.11	vm_get_property_list	80
3.11.11.1	Description	80
3.11.11.2	ACLs	80
3.11.11.3	Parameters	80
3.11.11.4	Examples	80
3.11.12	vm_create_property_list	81
3.11.12.1	Description	81
3.11.12.2	ACLs	81
3.11.12.3	Parameters	81
3.11.12.4	Examples	81

3.11.13 vm_delete_property_list	81
3.11.13.1 Description	81
3.11.13.2 ACLs	81
3.11.13.3 Parameters	81
3.11.13.4 Examples	82
3.11.14 osf_get_property_list	82
3.11.14.1 Description	82
3.11.14.2 ACLs	82
3.11.14.3 Parameters	82
3.11.14.4 Examples	82
3.11.15 osf_create_property_list	83
3.11.15.1 Description	83
3.11.15.2 ACLs	83
3.11.15.3 Parameters	83
3.11.15.4 Examples	83
3.11.16 osf_delete_property_list	83
3.11.16.1 Description	83
3.11.16.2 ACLs	84
3.11.16.3 Parameters	84
3.11.16.4 Examples	84
3.11.17 di_get_property_list	84
3.11.17.1 Description	84
3.11.17.2 ACLs	84
3.11.17.3 Parameters	84
3.11.17.4 Examples	85
3.11.18 di_create_property_list	85
3.11.18.1 Description	85
3.11.18.2 ACLs	85
3.11.18.3 Parameters	85
3.11.18.4 Examples	85
3.11.19 di_delete_property_list	86
3.11.19.1 Description	86
3.11.19.2 ACLs	86
3.11.19.3 Parameters	86
3.11.19.4 Examples	86
3.12 Views	86
3.12.1 tenant_view_get_list	86
3.12.1.1 Description	86
3.12.1.2 ACLs	86

3.12.1.3	Parameters	86
3.12.1.4	Examples	87
3.12.2	tenant_property_view_set	87
3.12.2.1	Description	87
3.12.2.2	ACLs	88
3.12.2.3	Parameters	88
3.12.2.4	Examples	88
3.12.3	tenant_attribute_view_set	88
3.12.3.1	Description	88
3.12.3.2	ACLs	88
3.12.3.3	Parameters	88
3.12.3.4	Examples	89
3.12.4	tenant_view_reset	89
3.12.4.1	Description	89
3.12.4.2	ACLs	89
3.12.4.3	Parameters	89
3.12.4.4	Examples	89
3.12.5	admin_property_view_set	90
3.12.5.1	Description	90
3.12.5.2	ACLs	90
3.12.5.3	Parameters	90
3.12.5.4	Examples	90
3.12.6	admin_attribute_view_set	90
3.12.6.1	Description	90
3.12.6.2	ACLs	90
3.12.6.3	Parameters	90
3.12.6.4	Examples	91
3.12.7	admin_view_reset	91
3.12.7.1	Description	91
3.12.7.2	ACLs	91
3.12.7.3	Parameters	91
3.12.7.4	Examples	91
3.13	Statistics	92
3.13.1	qvd_objects_statistics	92
3.13.1.1	Description	92
3.13.1.2	ACLs	92
3.13.1.3	Channels	92
3.13.1.4	Parameters	92
3.13.1.5	Examples	92
3.14	Error Codes	93

The QVD API lets you administrate the different components that make up QVD.

1 Paths

The following table shows the different URIs of the API to which you can access:

Table 1: Routes API

PROTOCOL	URI	VERBS	DESCRIPTION
HTTPS	/api/info	POST GET	Returns public information about the API and does not require authentication. Said information is: <ul style="list-style-type: none"> • Date of the server in UTC format • Multitenant mode is activated or not • API version • Diverse public configuration parameters
HTTPS	/api	POST GET	This is the main route to access the functions of the API. The information returned depends on the action introduced. These actions are described in the section [api]
HTTPS	/api/login	POST	With this path some credentials for a temporary session can be generated
HTTPS	/api/logout	POST	Path to delete the credentials of the temporary session that is currently being used
WSS	/api/staging		Any change in the system is reported through this web socket.
HTTPS	/api/di/upload	POST OPTIONS	Upload a disk image from your local machine
WSS	/api/di/download		With this web socket you can know the status when asking for the download of an image from a URL.

2 Types

The types for the different parameters of the API are the following:

Table 2: Types API

TYPE	DEFINITION	EXAMPLE
string		"string"
integer		10
token	string defined in a concrete action	"id"
regex	string with a chain to do the matching. If % is used at the beginning and at the end the matching will be applied to the results that contain the string	"%vm%"

Table 2: (continued)

TYPE	DEFINITION	EXAMPLE
op	"~" "="	
	"<"	
	">"	
	"←"	
	">="	
	"!="	
	"<>"	
cond	"-or" "-and"	
order	"-asc" "-desc"	
var	string integer	
hash	{string : var, ... }	{"key1":10,"key2":"value" }
array	[var, ...]	["string", 10]
token_hash	{token : var, ... }	{"id":10,"name":"admin" }
token_array	[token, ...]	["id", "name"]
filter_list	{filter, ... }	{"-or":["id",10,"name","admin"],"id":10}
filter	token : var cond : filter_array token : array token : {op : regex }	"id":10 "-or":["id",10,"name","admin"] "id" : ["1000","2000","3000"] "name" : {"~" : "%vm%" }
filter_array	[token, var, token, var, ...]	["id",10,"name","admin"]
order_list	{"field" : token, "order" : order} {"field" : token_array, "order" : order}	{"field":"id","order":"-desc"} {"field":["id","name"],"order":"-asc" }

3 /api

Firstly, to access the API it is necessary to authenticate the user and to do so, there are two possibilities: * Implicit authentication. Use the login path to generate some credentials that are managed using cookies. After a satisfactory authentication, any request that is made to the API will be processed. And finally the logout path will be called to eliminate the credentials. * Explicit authentication. Specifying the authentication credentials in any of the calls of the API.

In both methods, it is necessary to specify the parameters "login" and "password" (and "tenant" if the multitenant mode is activated) or to provide the session id generated in a previous consultation using in this case the parameter "sid".



Note

It is strongly recommended to use the first method of authentication so as not to store the credentials in the history and that such credentials are being sent in each request.

Moreover all the calls to this API path require at the very least the parameter "action" in the URI and the list of possible values that this field can take are specified in this section. A call to the API could be, for example:

```
GET https://myqvd.theqvd.com/api?action=current_admin_setup&sid= ↔
ffc6097dc66a0ba748384bab4b3f18764c950106
```

```
GET https://myqvd.theqvd.com/api?action=current_admin_setup&login=myadmin&password=myspw& ↔
tenant=mytenant
```


All the actions return the status code HTTP 200 with a message JSON. If everything has gone well, the JSON generated will contain a field "status" with value 0 and the desired fields in the request. Alternatively, the field "status" will contain a value different from 0 with a message about the error and additional information.

- **OK**

```
{
  "sid": "29f91648cd2ecc9cb5a138dbb42d9f6804e0cdad",
  "status": 0,
  "total": 0,
  "rows": [],
  "message": "Successful completion"
}
```

- **ERROR**

```
{
  "additional_info": "No additional information",
  "status": 3100,
  "message": "No credentials provided for authentication"
}
```

Below is the complete list of accepted parameters for each action of the API. For each parameter, we specify its type, defined above, and each of the accepted tokens for each parameter with the necessary ACLs to be able to use it. If the token is compulsory it will be shown underlined>



Note

The token "tenant_id" is always compulsory if requests are made to the Api as superadministrator and the multitenant mode is active. In any other case it is not necessary.

3.1 Login

3.2 ACLs

3.2.1 acl_get_list

3.2.1.1 Description

Returns the parameters of a list of ACLs

3.2.1.2 ACLs

- role.see.acl-list
- administrator.see.acl-list

3.2.1.3 Parameters

Parameter	Token	ACL
filters	id	
<filter_list>	name	
	description	

Parameter	Token	ACL
	acl_name	
	admin_id	
	operative	
fields <token_array>	id	
	name	
	description	
	roles	
	operative	
order_by <order_list>	id	
	name	
	description	

3.2.1.4 Examples

- Input:

```
action=acl_get_list&filters={"id":1}
```

- Output:

```
{
  "total" : 1,
  "message" : "Successful completion",
  "status" : 0,
  "rows" : [
    {
      "roles" : {
        "43" : "Root"
      },
      "description" : "Create administrators",
      "name" : "administrator.create.",
      "id" : 1,
      "operative" : 1
    }
  ]
}
```

3.2.2 get_acls_in_roles

3.2.2.1 Description

Returns the parameters of a list of ACLs

3.2.2.2 ACLs

- administrator.see.acl-list

3.2.2.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	

Parameter	Token	ACL
	description	
	acl_name	
	role_id	
	operative	
fields <token_array>	id	
	name	
	description	
	roles	
	operative	
order_by <order_list>	id	
	name	
	description	

3.2.2.4 Examples

- Input:

```
action=get_acls_in_roles
```

- Output:

```
{}
```

3.2.3 get_acls_in_admins

3.2.3.1 Description

Returns the parameters of a list of ACLs

3.2.3.2 ACLs

- administrator.see.acl-list

3.2.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	description	
	acl_name	
	admin_id	
	operative	
fields <token_array>	id	
	name	
	description	
	roles	
	operative	
order_by <order_list>	id	
	name	
	description	

3.2.3.4 Examples

- Input:

```
action=get_acls_in_admins
```

- Output:

```
{}
```

3.2.4 acl_tiny_list

3.2.4.1 Description

Returns a subset of parameters of a list of ACLs

3.2.4.2 ACLs

- role.see.acl-list
- administrator.see.acl-list

3.2.4.3 Parameters

Parameter	Token	ACL
filters <filter_list>	name	
fields <token_array>	id	
	name	
order_by <order_list>	id	
	name	
	description	

3.2.4.4 Examples

- Input:

```
action=acl_tiny_list
```

- Output:

```
{
  "total" : 3,
  "status" : 0,
  "message" : "Successful completion",
  "rows" : [
    {
      "id" : 1,
      "name" : "administrator.create."
    },
    {
```

```

    "name" : "administrator.create.language",
    "id" : 2
  },
  {
    "name" : "administrator.delete.",
    "id" : 3
  }
]
}

```

3.2.5 number_of_acls_in_role

3.2.5.1 Description

Returns the number of acls in a role

3.2.5.2 ACLs

- administrator.see.acl-list

3.2.5.3 Parameters

Parameter	Token	ACL
filters <filter_list>	role_id	

3.2.5.4 Examples

- Input:

```
action=number_of_acls_in_role&filters={"role_id":1}
```

- Output:

```

{
  "%" : {
    "total" : 309,
    "effective" : 2
  },
  "status" : 0,
  "message" : "Successful completion"
}

```

3.2.6 number_of_acls_in_admin

3.2.6.1 Description

Returns the number of acls in an administrator

3.2.6.2 ACLs

- administrator.see.acl-list

3.2.6.3 Parameters

Parameter	Token	ACL
filters <filter_list>	admin_id	

3.2.6.4 Examples

- Input:

```
action=number_of_acls_in_admin&filters={"admin_id":1}
```

- Output:

```
{
  "%": {
    "effective": 309,
    "total": 309
  },
  "status": 0,
  "message": "Successful completion"
}
```

3.3 Roles

3.3.1 role_get_list

3.3.1.1 Description

Returns the parameters of a list of roles

3.3.1.2 ACLs

- role.see-main.

3.3.1.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	
	fixed	
	internal	
	creation_date	role.filter.creation-date
	creation_admin_id	role.filter.created-by
creation_admin_name	role.filter.created-by	
fields <token_array>	id	
	name	
	description	role.see.description
	acls	role.see.acls

Parameter	Token	ACL
	roles	role.see.roles
	fixed	
	internal	
	creation_date	role.filter.creation-date
	creation_admin_id	role.filter.created-by
	creation_admin_name	role.filter.created-by
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	role.see.description
	fixed	
	internal	
	creation_date	role.filter.creation-date
	creation_admin_id	role.filter.created-by
	creation_admin_name	role.filter.created-by

3.3.1.4 Examples

- Input:

```
action=role_get_list&filters={"id":1}
```

- Output:

```
{
  "message" : "Successful completion",
  "total" : 1,
  "rows" : [
    {
      "internal" : 1,
      "name" : "Administrators Creator",
      "id" : 1,
      "tenant_name" : "-",
      "acls" : {
        "positive" : [
          "administrator.create.",
          "administrator.create.language"
        ],
        "negative" : []
      },
      "description" : null,
      "creation_admin_name" : null,
      "tenant_id" : -1,
      "creation_date" : null,
      "creation_admin_id" : null,
      "fixed" : 1,
      "roles" : {}
    }
  ],
  "status" : 0
}
```

3.3.2 role_get_details

3.3.2.1 Description

Returns all the parameters of a role

3.3.2.2 ACLs

- role.see-details

3.3.2.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	
fields <token_array>	id	
	name	
	description	role.see.description
	acls	role.see.acls
	roles	role.see.roles
	fixed	
	internal	
	creation_date	role.filter.creation-date
	creation_admin_id	role.filter.created-by
	creation_admin_name	role.filter.created-by
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	role.see.description
	fixed	
	internal	
	creation_date	role.filter.creation-date
	creation_admin_id	role.filter.created-by
	creation_admin_name	role.filter.created-by

3.3.2.4 Examples

- Input:

```
action=role_get_details&filters={"id":1}
```

- Output:

```
{
  "message" : "Successful completion",
  "rows" : [
    {
      "tenant_name" : "-",
      "id" : 1,
      "name" : "Administrators Creator",
      "internal" : 1,
      "roles" : {},
      "fixed" : 1,

```



```

    "creation_date" : null,
    "creation_admin_id" : null,
    "tenant_id" : -1,
    "creation_admin_name" : null,
    "acls" : {
      "negative" : [],
      "positive" : [
        "administrator.create.",
        "administrator.create.language"
      ]
    },
    "description" : null
  }
],
"total" : 1,
"status" : 0
}

```

3.3.3 role_tiny_list

3.3.3.1 Description

Returns a subset of the parameters of a list of roles

3.3.3.2 ACLs

- administrator.see.roles
- role.see.inherited-roles
- tenant.purge.

3.3.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	id	
	name	
	tenant_name	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	role.see.description
	fixed	
	internal	
	creation_date	role.filter.creation-date
	creation_admin_id	role.filter.created-by
creation_admin_name	role.filter.created-by	

3.3.3.4 Examples

- Input:

```
action=role_tiny_list
```

- Output:

```
{
  "rows" : [
    {
      "tenant_name" : "-",
      "id" : 1,
      "name" : "Administrators Creator"
    }
  ],
  "total" : 1,
  "message" : "Successful completion",
  "status" : 0
}
```

3.3.4 role_all_ids

3.3.4.1 Description

Returns the ids of the roles

3.3.4.2 ACLs

- role.see-main.
- role.-massive.

3.3.4.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	
	fixed	
	internal	
	creation_date	role.filter.creation-date
	creation_admin_id	role.filter.created-by
creation_admin_name	role.filter.created-by	
fields <token_array>	id	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	role.see.description
	fixed	
	internal	
	creation_date	role.filter.creation-date
	creation_admin_id	role.filter.created-by
creation_admin_name	role.filter.created-by	

3.3.4.4 Examples

- Input:

```
action=role_all_ids
```

- Output:

```
{
  "status" : 0,
  "rows" : [
    1,
    2
  ],
  "total" : 2,
  "message" : "Successful completion"
}
```

3.3.5 role_create

3.3.5.1 Description

Creates a role

3.3.5.2 ACLs

- role.create.

3.3.5.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	name	
	description	
	tenant_id	
	fixed	
	internal	
	__acls__	role.update.assign-acl
	__roles__	role.update.assign-role

3.3.5.4 Examples

- Input:

```
action=create_role&arguments={"name":"Rol"}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "rows" : [
```

```

    {
      "id" : 10004
    }
  ],
  "message" : "Successful completion"
}

```

3.3.6 role_update

3.3.6.1 Description

Updates a role

3.3.6.2 ACLs

- role.update.

3.3.6.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
arguments <token_hash>	name	role.update.name
	description	role.update.description
	__acls_changes__ : assign_acls	role.update.assign_acl
	__acls_changes__ : unassign_acls	role.update.assign_acl
	__roles_changes__ : assign_acls	role.update.assign_role
	__roles_changes__ : unassign_acls	role.update.assign_role

3.3.6.4 Examples

- Input:

```
action=role_update&filters={"id":10000}&arguments={"description":"myrole"}
```

- Output:

```

{
  "status" : 0,
  "message" : "Successful completion",
  "rows" : [],
  "total" : 1
}

```

3.3.7 role_delete

3.3.7.1 Description

Deletes a role

3.3.7.2 ACLs

- role.delete.
- tenant.purge.

3.3.7.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	

3.3.7.4 Examples

- Input:

```
action=role_delete&filters={"id":10000}
```

- Output:

```
{
  "status" : 0,
  "rows" : [],
  "total" : 1,
  "message" : "Successful completion"
}
```

3.4 Tenants

3.4.1 tenant_get_list

3.4.1.1 Description

Returns the parameters of a list of tenants

3.4.1.2 ACLs

- tenant.see-main.

3.4.1.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	description	
	block	
	language	
	blocked	tenant.filter.block
	creation_date	tenant.filter.creation-date
	creation_admin_id	tenant.filter.created-by
creation_admin_name	tenant.filter.created-by	

Parameter	Token	ACL
fields <token_array>	id	
	name	
	description	tenant.see.description
	block	tenant.see.blocksize
	language	tenant.see.language
	blocked	tenant.see.block
	creation_date	tenant.see.creation-date
	creation_admin_id	tenant.see.created-by
order_by <order_list>	id	
	name	
	description	tenant.see.description
	block	tenant.see.blocksize
	language	tenant.see.language
	blocked	tenant.see.block
	creation_date	tenant.see.creation-date
	creation_admin_id	tenant.see.created-by
creation_admin_name	tenant.see.created-by	

3.4.1.4 Examples

- Input:

```
action=tenant_get_list
```

- Output:

```
{
  "rows" : [
    {
      "creation_admin_id" : 1,
      "block" : 10,
      "language" : "auto",
      "creation_date" : "2016-02-17T16:14:54",
      "id" : 1,
      "creation_admin_name" : "superadmin",
      "name" : "default",
      "blocked" : 0,
      "description" : "tenant1"
    },
    {
      "block" : 10,
      "language" : "auto",
      "creation_date" : "2016-03-04T09:49:42",
      "id" : 10005,
      "creation_admin_name" : "superadmin",
      "creation_admin_id" : 1,
      "description" : null,
      "blocked" : 0,
      "name" : "demo"
    },
    {
      "creation_admin_name" : "superadmin",
      "block" : 10,
      "language" : "auto",
      "creation_date" : "2016-03-08T14:48:31",
```

```

    "id" : 10006,
    "creation_admin_id" : 1,
    "blocked" : 0,
    "description" : null,
    "name" : "tenantdoc"
  }
],
"message" : "Successful completion",
"status" : 0,
"total" : 3
}

```

3.4.2 tenant_get_details

3.4.2.1 Description

Returns all the parameters of a list of tenants

3.4.2.2 ACLs

- tenant.see-details.

3.4.2.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	description	
	block	
	language	
	blocked	tenant.filter.block
	creation_date	tenant.filter.creation-date
	creation_admin_id	tenant.filter.created-by
fields <token_array>	creation_admin_name	tenant.filter.created-by
	id	
	name	
	description	tenant.see.description
	block	tenant.see.blocksize
	language	tenant.see.language
	blocked	tenant.see.block
	creation_date	tenant.see.creation-date
order_by <order_list>	creation_admin_id	tenant.see.created-by
	creation_admin_name	tenant.see.created-by
	id	
	name	
	description	tenant.see.description
	block	tenant.see.blocksize
	language	tenant.see.language
	blocked	tenant.see.block
creation_date	tenant.see.creation-date	

3.4.2.4 Examples

- Input:

```
action=tenant_get_details&filters={"id":10006}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "message" : "Successful completion",
  "rows" : [
    {
      "blocked" : 0,
      "description" : null,
      "name" : "tenantdoc",
      "id" : 10006,
      "creation_date" : "2016-03-08T14:48:31",
      "language" : "auto",
      "block" : 10,
      "creation_admin_name" : "superadmin",
      "creation_admin_id" : 1
    }
  ]
}
```

3.4.3 tenant_tiny_list

3.4.3.1 Description

Returns a small subset of parameters of the tenants

3.4.3.2 ACLs

- tenant.see-main.

3.4.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	description	
	block	
	language	
	blocked	tenant.filter.block
	creation_date	tenant.filter.creation-date
	creation_admin_id	tenant.filter.created-by
fields <token_array>	id	
	name	
order_by <order_list>	id	
	name	
	description	tenant.see.description

Parameter	Token	ACL
	block	tenant.see.blocksize
	language	tenant.see.language
	blocked	tenant.see.block
	creation_date	tenant.see.creation-date
	creation_admin_id	tenant.see.created-by
	creation_admin_name	tenant.see.created-by

3.4.3.4 Examples

- Input:

```
action=tenant_tiny_list&order_by={"field":"id","order":"-asc"}
```

- Output:

```
{
  "rows" : [
    {
      "id" : 0,
      "name" : "*"
    },
    {
      "id" : 1,
      "name" : "default"
    },
    {
      "id" : 10005,
      "name" : "demo"
    },
    {
      "id" : 10006,
      "name" : "tenantdoc"
    }
  ],
  "message" : "Successful completion",
  "total" : 4,
  "status" : 0
}
```

3.4.4 tenant_all_ids

3.4.4.1 Description

Returns all tenant ids

3.4.4.2 ACLs

- tenant.-massive.
- tenant.see-main.

3.4.4.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	description	
	block	
	language	
	blocked	tenant.filter.block
	creation_date	tenant.filter.creation-date
	creation_admin_id	tenant.filter.created-by
	creation_admin_name	tenant.filter.created-by
fields <token_array>	id	
order_by <order_list>	id	
	name	
	description	tenant.see.description
	block	tenant.see.blocksize
	language	tenant.see.language
	blocked	tenant.see.block
	creation_date	tenant.see.creation-date
	creation_admin_id	tenant.see.created-by
	creation_admin_name	tenant.see.created-by

3.4.4.4 Examples

- Input:

```
action=tenant_all_ids
```

- Output:

```
{
  "status" : 0,
  "total" : 4,
  "message" : "Successful completion",
  "rows" : [
    0,
    1,
    10005,
    10006
  ]
}
```

3.4.5 tenant_create

3.4.5.1 Description

Creates a new tenant

3.4.5.2 ACLs

- tenant.create.

3.4.5.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	name	
	description	
	block	
	language	
	blocked	

3.4.5.4 Examples

- Input:

```
action=tenant_create&arguments={"name":"new_tenant","block":"10","language":"es"}
```

- Output:

```
{
  "total" : 1,
  "status" : 0,
  "rows" : [
    {
      "id" : 10007
    }
  ],
  "message" : "Successful completion"
}
```

3.4.6 tenant_update

3.4.6.1 Description

Updates the parameters of a tenant

3.4.6.2 ACLs

- tenant.update.*

3.4.6.3 Parameters

Parameter	Token	ACL
filters <token_hash>	id	
arguments <token_hash>	name	
	description	tenant.update.description
	block	tenant.update.blocksize
	language	tenant.update.language
	blocked	tenant.update.block

3.4.6.4 Examples

- Input:

```
action=tenant_update&filters={"id":"1"}&arguments={"description":"Main tenant"}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "rows" : [],
  "message" : "Successful completion"
}
```

3.4.7 tenant_delete

3.4.7.1 Description

Deletes one tenant

3.4.7.2 ACLs

- tenant.delete.

3.4.7.3 Parameters

Parameter	Token	ACL
filters <token_hash>	id	

3.4.7.4 Examples

- Input:

```
action=tenant_delete&filters={"id":"10007"}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "rows" : [],
  "message" : "Successful completion"
}
```

3.4.8 mytenant_update

3.4.8.1 Description

Updates the current tenant

3.4.8.2 ACLs

- config.wat.

3.4.8.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	name	
	description	
	block	
	language	

3.4.8.4 Examples

- Input:

```
action=mytenant_update&arguments={"description":"Main tenant"}
```

- Output:

```
{
  "total" : 1,
  "status" : 0,
  "rows" : [],
  "message" : "Successful completion"
}
```

3.5 Administrators

3.5.1 current_admin_setup

3.5.1.1 Description

Returns the setup for the logged administrator

3.5.1.2 ACLs

3.5.1.3 Parameters

Parameter	Token	ACL
-----------	-------	-----

3.5.1.4 Examples

- Input:

```
action=current_admin_setup
```

- Output:

```
{
  "admin_language" : "en",
  "acls" : [
    "administrator.create."
  ],
  "tenant_id" : 0,
  "admin_block" : 10,
  "tenant_name" : "*"
}
```

```

"server_datetime" : "Tue Mar 15 15:12:19 2016",
"tenant_language" : "auto",
"message" : "Successful completion",
"views" : [],
"status" : 0,
"tenant_block" : 10,
"admin_name" : "myadmin",
"admin_id" : 1,
"multitenant" : "1"
}

```

3.5.2 administrator_get_list

3.5.2.1 Description

Returns the parameters of a list of administrators

3.5.2.2 ACLs

- administrator.see-main.

3.5.2.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	
	block	
	language	
	creation_date	administrator.filter.creation-date
	creation_admin_id	administrator.filter.created-by
creation_admin_name	administrator.filter.created-by	
fields <token_array>	id	
	tenant_id	
	tenant_name	
	name	
	description	administrator.see.description
	roles	administrator.see.roles
	block	
	language	administrator.see.language
	creation_date	administrator.see.creation-date
	creation_admin_id	administrator.see.created-by
creation_admin_name	administrator.see.created-by	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	administrator.see.description
	block	
	language	administrator.see.language
	creation_date	administrator.see.creation-date
	creation_admin_id	administrator.see.created-by
	creation_admin_name	administrator.see.created-by

3.5.2.4 Examples

- Input:

```
action=administrator_get_list
```

- Output:

```
{
  "rows" : [
    {
      "creation_admin_name" : "superadmin",
      "roles" : {
        "43" : "Root"
      },
      "description" : null,
      "language" : "en",
      "creation_admin_id" : 1,
      "creation_date" : "2016-02-17T16:14:54",
      "tenant_name" : "*",
      "id" : 1,
      "name" : "superadmin",
      "block" : 10,
      "tenant_id" : 0
    },
    {
      "block" : 10,
      "tenant_id" : 1,
      "tenant_name" : "default",
      "id" : 2,
      "name" : "admin",
      "creation_date" : "2016-02-17T16:14:54",
      "creation_admin_id" : 1,
      "language" : "auto",
      "description" : null,
      "roles" : {
        "43" : "Root"
      },
      "creation_admin_name" : "superadmin"
    },
    {
      "description" : null,
      "language" : "auto",
      "roles" : {
        "43" : "Root"
      },
      "creation_admin_name" : "superadmin",
      "creation_date" : "2016-03-04T09:49:45",
      "creation_admin_id" : 1,
      "block" : 10,
      "tenant_id" : 10005,
      "id" : 10004,
      "tenant_name" : "demo",
      "name" : "admin"
    }
  ],
  "status" : 0,
  "total" : 3,
  "message" : "Successful completion"
}
```

3.5.3 administrator_get_details

3.5.3.1 Description

Returns all the parameters of an administrator

3.5.3.2 ACLs

- administrator.see-details.*

3.5.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
fields <token_array>	id	
	tenant_id	
	tenant_name	
	name	
	description	administrator.see.description
	roles	administrator.see.roles
	block	
	language	administrator.see.language
	creation_date	administrator.see.creation-date
	creation_admin_id	administrator.see.created-by
creation_admin_name	administrator.see.created-by	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	administrator.see.description
	block	
	language	administrator.see.language
	creation_date	administrator.see.creation-date
	creation_admin_id	administrator.see.created-by
	creation_admin_name	administrator.see.created-by

3.5.3.4 Examples

- Input:

```
action=administrator_get_details&filters={"id":1}
```

- Output:

```
{
  "rows" : [
    {
      "roles" : {
        "43" : "Root "
      },
      "creation_admin_name" : "superadmin",
      "description" : null,
      "language" : "en",
    }
  ]
}
```



```

    "creation_admin_id" : 1,
    "creation_date" : "2016-02-17T16:14:54",
    "id" : 1,
    "name" : "superadmin",
    "tenant_name" : "*",
    "block" : 10,
    "tenant_id" : 0
  }
],
"total" : 1,
"message" : "Successful completion",
"status" : 0
}

```

3.5.4 administrator_tiny_list

3.5.4.1 Description

Returns a small subset of parameters of the administrators

3.5.4.2 ACLs

- log.filter.administrator
- *.filter.created-by

3.5.4.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	tenant_id	
	id	
	name	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	administrator.see.description
	block	
	language	administrator.see.language
	creation_date	administrator.see.creation-date
	creation_admin_id	administrator.see.created-by
creation_admin_name	administrator.see.created-by	

3.5.4.4 Examples

- Input:

```
action=administrator_tiny_list
```

- Output:

```

{
  "rows" : [
    {
      "id" : 2,
      "tenant_name" : "default",
      "name" : "admin"
    },
    {
      "id" : 10004,
      "tenant_name" : "demo",
      "name" : "admin"
    },
    {
      "tenant_name" : "*",
      "id" : 1,
      "name" : "superadmin"
    }
  ],
  "message" : "Successful completion",
  "total" : 3,
  "status" : 0
}

```

3.5.5 administrator_all_ids

3.5.5.1 Description

Returns all administrator IDs

3.5.5.2 ACLs

- administrator.-massive.
- administrator.see-main.

3.5.5.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	
	block	
	language	
	creation_date	administrator.filter.creation-date
	creation_admin_id	administrator.filter.created-by
creation_admin_name	administrator.filter.created-by	
fields <token_array>	id	
order_by <order_list>	id	
	tenant_id	
	tenant_name	
	name	
	description	administrator.see.description

Parameter	Token	ACL
	block	
	language	administrator.see.language
	creation_date	administrator.see.creation-date
	creation_admin_id	administrator.see.created-by
	creation_admin_name	administrator.see.created-by

3.5.5.4 Examples

- Input:

```
action=administrator_all_ids
```

- Output:

```
{
  "status" : 0,
  "message" : "Successful completion",
  "total" : 3,
  "rows" : [
    2,
    1,
    10004
  ]
}
```

3.5.6 administrator_create

3.5.6.1 Description

Creates administrator

3.5.6.2 ACLs

- administrator.create.

3.5.6.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	tenant_id	
	name	
	password	
	description	
	block	
	language	
	__roles__	administrator.update.assign-role

3.5.6.4 Examples

- Input:

```
action=administrator_create&arguments={"name":"myadmin","password":"123123"}
```

- Output:

```
{
  "rows" : [
    {
      "id" : 10006
    }
  ],
  "total" : 1,
  "message" : "Successful completion",
  "status" : 0
}
```

3.5.7 administrator_update

3.5.7.1 Description

Updates administrator

3.5.7.2 ACLs

- administrator.update.

3.5.7.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	
arguments <token_hash>	name	
	password	administrator.update.password
	description	administrator.update.description
	block	
	language	administrator.update.language
	__roles_changes__ : assign_roles	administrator.update.assign-role
	__roles_changes__ : unassign_roles	administrator.update.assign-role

3.5.7.4 Examples

- Input:

```
action=administrator_update&filters={"id":10006}&arguments={"description":"myadmin"}
```

- Output:

```
{
  "total" : 1,
  "message" : "Successful completion",
  "status" : 0,
  "rows" : []
}
```

3.5.8 administrator_delete

3.5.8.1 Description

Deletes administrator

3.5.8.2 ACLs

- administrator.delete.

3.5.8.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	

3.5.8.4 Examples

- Input:

```
action=administrator_delete&filters={"id":10006}
```

- Output:

```
{
  "message" : "Successful completion",
  "total" : 1,
  "status" : 0,
  "rows" : []
}
```

3.5.9 myadmin_update

3.5.9.1 Description

Updates current administrator

3.5.9.2 ACLs

3.5.9.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	name	
	password	
	description	
	block	
	language	

3.5.9.4 Examples

- Input:

```
action=myadmin_update&arguments={"description":"myadmin"}
```

- Output:

```
{
  "rows" : [],
  "message" : "Successful completion",
  "total" : 1,
  "status" : 0
}
```

3.6 Users

3.6.1 user_get_list

3.6.1.1 Description

Returns the parameters of a list of users

3.6.1.2 ACLs

- user.see-main.
- *.see.user-list

3.6.1.3 Channels

- user_created
- user_deleted
- user_changed
- vm_created
- vm_deleted

3.6.1.4 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	user.filter.description
	blocked	user.filter.block
	creation_date	user.filter.creation-date
	creation_admin_id	user.filter.created-by
	creation_admin_name	user.filter.created-by
fields <token_array>	id	
	name	
	tenant_id	
	tenant_name	
	description	user.see.description

Parameter	Token	ACL
	blocked	user.see.block
	number_of_vms	user.see.vms-info
	number_of_vms_connected	user.see.vm-list-state
	properties	user.see.properties
	creation_date	user.see.creation_date
	creation_admin_id	user.see.created_by
	creation_admin_name	user.see.created_by
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	user.see.description
	blocked	user.see.block
	creation_date	user.see.creation_date
	creation_admin_id	user.see.created_by
	creation_admin_name	user.see.created_by

3.6.1.5 Examples

- Input:

```
action=user_get_list
```

- Output:

```
{
  "total" : 2,
  "message" : "Successful completion",
  "rows" : [
    {
      "number_of_vms_connected" : "0",
      "id" : 10005,
      "tenant_name" : "demo",
      "creation_admin_id" : 1,
      "description" : null,
      "creation_admin_name" : "superadmin",
      "creation_date" : "2016-03-04T09:49:47",
      "name" : "user",
      "tenant_id" : 10005,
      "properties" : {},
      "number_of_vms" : "1",
      "blocked" : 0
    },
    {
      "creation_admin_name" : "superadmin",
      "number_of_vms_connected" : "0",
      "id" : 10001,
      "tenant_name" : "default",
      "creation_admin_id" : 1,
      "description" : null,
      "properties" : {},
      "blocked" : 0,
      "number_of_vms" : "2",
      "name" : "zarzuelo",
      "creation_date" : "2016-03-03T15:18:38",
      "tenant_id" : 1
    }
  ]
}
```

```

    }
  ],
  "status" : 0
}

```

3.6.2 user_get_details

3.6.2.1 Description

Returns all the parameters of an user

3.6.2.2 ACLs

- user.see-details.

3.6.2.3 Channels

- user_created
- user_deleted
- user_changed
- vm_created
- vm_deleted

3.6.2.4 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
fields <token_array>	id	
	name	
	tenant_id	
	tenant_name	
	description	user.see.description
	blocked	user.see.block
	number_of_vms	user.see.vms-info
	number_of_vms_connected	user.see.vm-list-state
	properties	user.see.properties
	creation_date	user.see.creation_date
creation_admin_id	user.see.created_by	
creation_admin_name	user.see.created_by	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	user.see.description
	blocked	user.see.block
	creation_date	user.see.creation_date
	creation_admin_id	user.see.created_by
creation_admin_name	user.see.created_by	

3.6.2.5 Examples

- Input:

```
action=user_get_details&filters={"id":10005}
```

- Output:

```
{
  "message" : "Successful completion",
  "total" : 1,
  "rows" : [
    {
      "creation_admin_name" : "superadmin",
      "description" : null,
      "id" : 10005,
      "creation_admin_id" : 1,
      "tenant_name" : "demo",
      "number_of_vms_connected" : "0",
      "number_of_vms" : "1",
      "blocked" : 0,
      "properties" : {},
      "tenant_id" : 10005,
      "name" : "user",
      "creation_date" : "2016-03-04T09:49:47"
    }
  ],
  "status" : 0
}
```

3.6.3 user_tiny_list

3.6.3.1 Description

Returns a small subset of parameters of the list of users

3.6.3.2 ACLs

- vm.create.
- vm.filter.user
- tenant.purge

3.6.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	tenant_name	
	id	
	name	
order_by <order_list>	id	
	name	
	tenant_id	

Parameter	Token	ACL
	tenant_name	
	description	user.see.description
	blocked	user.see.block
	creation_date	user.see.creation_date
	creation_admin_id	user.see.created_by
	creation_admin_name	user.see.created_by

3.6.3.4 Examples

- Input:

```
action=user_tiny_list
```

- Output:

```
{
  "total" : 2,
  "message" : "Successful completion",
  "rows" : [
    {
      "name" : "user",
      "id" : 10005,
      "tenant_name" : "demo"
    },
    {
      "tenant_name" : "default",
      "id" : 10001,
      "name" : "zarzuelo"
    }
  ],
  "status" : 0
}
```

3.6.4 user_all_ids

3.6.4.1 Description

Returns all users IDs

3.6.4.2 ACLs

- host.-massive.
- host.see-main.

3.6.4.3 Parameters

Parameter	Token	ACL
filters	id	
<filter_list>	name	user.filter.name
	description	
	tenant_id	
	tenant_name	

Parameter	Token	ACL
	blocked	
	creation_date	
	creation_admin_id	
	creation_admin_name	
fields <token_array>	id	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	user.see.description
	blocked	user.see.block
	creation_date	user.see.creation_date
	creation_admin_id	user.see.created_by
	creation_admin_name	user.see.created_by

3.6.4.4 Examples

- Input:

```
action=user_all_ids
```

- Output:

```
{
  "status" : 0,
  "rows" : [
    10005,
    10001
  ],
  "message" : "Successful completion",
  "total" : 2
}
```

3.6.5 user_get_state

3.6.5.1 Description

Returns user state

3.6.5.2 ACLs

- user.see.vm-list-state

3.6.5.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
fields <token_array>	number_of_vms_connected	user.see.vms-info
order_by <order_list>	id	

Parameter	Token	ACL
	name	
	tenant_id	
	tenant_name	
	description	user.see.description
	blocked	user.see.block
	creation_date	user.see.creation_date
	creation_admin_id	user.see.created_by
	creation_admin_name	user.see.created_by

3.6.5.4 Examples

- Input:

```
action=host_get_state&filters={"id":10000}
```

- Output:

```
{
  "rows" : [
    {
      "number_of_vms_connected" : null
    }
  ],
  "status" : 0,
  "total" : 1,
  "message" : "Successful completion"
}
```

3.6.6 user_create

3.6.6.1 Description

Creates an user

3.6.6.2 ACLs

- user.create.

3.6.6.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	tenant_id	
	name	
	password	
	description	
	blocked	
	__properties__	user.create.properties

3.6.6.4 Examples

- Input:

```
action=host_create&arguments={"name":"localhost","address":"10.3.15.1"}
```

- Output:

```
{
  "message" : "Successful completion",
  "total" : 1,
  "rows" : [
    {
      "id" : 10000
    }
  ],
  "status" : 0
}
```

3.6.7 user_update

3.6.7.1 Description

Updates an user

3.6.7.2 ACLs

- user.update.*

3.6.7.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	name	
	password	user.update.password
	description	user.update.description
	address	user.update.address
	blocked	user.update.blocked
	__properties_changes__ : set	user.update.properties
	__properties_changes__ : delete	user.update.properties
filters <filter_list>	id	

3.6.7.4 Examples

- Input:

```
action=user_update&arguments={"description":"User description"}&filters={"id":10000}
```

- Output:

```
{
  "status" : 0,
  "rows" : [],
}
```

```

    "total" : 1,
    "message" : "Successful completion"
  }

```

3.6.8 user_delete

3.6.8.1 Description

Deletes an user

3.6.8.2 ACLs

- user.delete.
- tenant.purge.

3.6.8.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	

3.6.8.4 Examples

- Input:

```
action=user_delete&filters={"id":10000}
```

- Output:

```

{
  "status" : 0,
  "rows" : [],
  "total" : 1,
  "message" : "Successful completion"
}

```

3.7 Hosts

3.7.1 host_get_list

3.7.1.1 Description

Returns the parameters of a list of hosts

3.7.1.2 ACLs

- host.see-main.

3.7.1.3 Channels

- host_created
- host_deleted
- host_changed
- vm_created
- vm_deleted

3.7.1.4 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	description	
	address	
	frontend	
	backend	
	vm_id	host.filter.vm
	state	host.filter.state
	blocked	host.filter.block
	creation_date	host.filter.creation-date
	creation_admin_id	host.filter.created-by
creation_admin_name	host.filter.created-by	
fields <token_array>	id	
	name	
	description	host.see.description
	address	host.see.address
	frontend	
	backend	
	state	host.see.state
	load	
	blocked	host.see.block
	number_of_vms_connected	host.see.vms-info
	properties	host.see.properties
	creation_date	host.see.creation-date
	creation_admin_id	host.see.created-by
	creation_admin_name	host.see.created-by
order_by <order_list>	id	
	name	
	description	host.see.description
	address	host.see.address
	state	host.see.state
	blocked	host.see.block
	creation_date	host.see.creation-date
	creation_admin_id	host.see.created-by
creation_admin_name	host.see.created-by	

3.7.1.5 Examples

- Input:

```
action=host_get_list
```

- Output:

```
{
  "rows" : [
    {
      "frontend" : 1,
      "blocked" : 0,
      "name" : "localhost",
      "id" : 10000,
      "description" : null,
      "creation_admin_id" : 1,
      "backend" : 1,
      "address" : "10.3.15.1",
      "creation_date" : "2016-03-03T14:06:14",
      "number_of_vms_connected" : "0",
      "creation_admin_name" : "superadmin",
      "state" : "running",
      "load" : null,
      "properties" : {}
    }
  ],
  "message" : "Successful completion",
  "status" : 0,
  "total" : 1
}
```

3.7.2 host_get_details

3.7.2.1 Description

Returns all the parameters of a list of hosts

3.7.2.2 ACLs

- host.see-details.
- host.see-main.

3.7.2.3 Channels

- host_created
- host_deleted
- host_changed
- vm_created
- vm_deleted

3.7.2.4 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
fields <token_array>	id	
	name	

Parameter	Token	ACL
	description	host.see.description
	address	host.see.address
	frontend	
	backend	
	state	host.see.state
	load	
	blocked	host.see.block
	number_of_vms_connected	host.see.vms-info
	properties	host.see.properties
	creation_date	host.see.creation-date
	creation_admin_id	host.see.created-by
creation_admin_name	host.see.created-by	
order_by <order_list>	id	
	name	
	description	host.see.description
	address	host.see.address
	state	host.see.state
	blocked	host.see.block
	creation_date	host.see.creation-date
	creation_admin_id	host.see.created-by
creation_admin_name	host.see.created-by	

3.7.2.5 Examples

- Input:

```
action=host_get_details&filters={"id":10000}
```

- Output:

```
{
  "rows" : [
    {
      "creation_date" : "2016-03-03T14:06:14",
      "number_of_vms_connected" : "0",
      "creation_admin_id" : 1,
      "description" : null,
      "backend" : 1,
      "address" : "10.3.15.1",
      "id" : 10000,
      "frontend" : 1,
      "blocked" : 0,
      "name" : "localhost",
      "properties" : {},
      "load" : null,
      "creation_admin_name" : "superadmin",
      "state" : "running"
    }
  ],
  "message" : "Successful completion",
  "total" : 1,
  "status" : 0
}
```

3.7.3 host_tiny_list

3.7.3.1 Description

Returns a small subset of parameters of the list of hosts

3.7.3.2 ACLs

- vm.filter.host

3.7.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>		
fields <token_array>	id	
	name	
order_by <order_list>	id	
	name	
	description	host.see.description
	address	host.see.address
	state	host.see.state
	blocked	host.see.block
	creation_date	host.see.creation-date
	creation_admin_id	host.see.created-by
creation_admin_name	host.see.created-by	

3.7.3.4 Examples

- Input:

```
action=host_tiny_list
```

- Output:

```
{
  "total" : 1,
  "status" : 0,
  "rows" : [
    {
      "name" : "localhost",
      "id" : 10000
    }
  ],
  "message" : "Successful completion"
}
```

3.7.4 host_all_ids

3.7.4.1 Description

Returns all host IDs

3.7.4.2 ACLs

- host.-massive.
- host.see-main.

3.7.4.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	description	
	address	
	frontend	
	backend	
	vm_id	host.filter.vm
	state	host.filter.state
	blocked	host.filter.block
	creation_date	host.filter.creation-date
	creation_admin_id	host.filter.created-by
creation_admin_name	host.filter.created-by	
fields <token_array>	id	
order_by <order_list>	id	
	name	
	description	host.see.description
	address	host.see.address
	state	host.see.state
	blocked	host.see.block
	creation_date	host.see.creation-date
	creation_admin_id	host.see.created-by
creation_admin_name	host.see.created-by	

3.7.4.4 Examples

- Input:

```
action=host_all_ids
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "message" : "Successful completion",
  "rows" : [
    10000
  ]
}
```

3.7.5 host_get_state

3.7.5.1 Description

Returns host state

3.7.5.2 ACLs

- host.see.vm-list-state

3.7.5.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
fields <token_array>	number_of_vms_connected	host.see.vms-info
order_by <order_list>	id	
	name	
	description	host.see.description
	address	host.see.address
	state	host.see.state
	blocked	host.see.block
	creation_date	host.see.creation-date
	creation_admin_id	host.see.created-by
creation_admin_name	host.see.created-by	

3.7.5.4 Examples

- Input:

```
action=host_get_state&filters={"id":10000}
```

- Output:

```
{
  "total" : 1,
  "status" : 0,
  "message" : "Successful completion",
  "rows" : [
    {
      "number_of_vms_connected" : 1
    }
  ]
}
```

3.7.6 host_create

3.7.6.1 Description

Creates a host

3.7.6.2 ACLs

- host.create.*

3.7.6.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	name	
	description	
	address	
	frontend	
	backend	
	state	
	blocked	
	__properties__	host.create.properties

3.7.6.4 Examples

- Input:

```
action=host_create&arguments={"name":"localhost","address":"10.3.15.1"}
```

- Output:

```
{
  "message" : "Successful completion",
  "rows" : [
    {
      "id" : 10000
    }
  ],
  "total" : 1,
  "status" : 0
}
```

3.7.7 host_update

3.7.7.1 Description

Updates a host

3.7.7.2 ACLs

- host.update.*

3.7.7.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	name	host.update.name
	description	host.update.description
	address	host.update.address
	blocked	host.update.blocked
	__properties_changes__ : set	host.update.properties
	__properties_changes__ : delete	host.update.properties
filters <filter_list>	id	

3.7.7.4 Examples

- Input:

```
action=host_update&arguments={"description":"Host description"}&filters={"id":10000}
```

- Output:

```
{
  "total" : 1,
  "status" : 0,
  "rows" : [],
  "message" : "Successful completion"
}
```

3.7.8 host_delete

3.7.8.1 Description

Deletes a host

3.7.8.2 ACLs

- host.delete.

3.7.8.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	

3.7.8.4 Examples

- Input:

```
action=host_delete&filters={"id":10000}
```

- Output:

```
{
  "total" : 1,
  "status" : 0,
  "message" : "Successful completion",
  "rows" : []
}
```

3.8 OSFs

3.8.1 osf_get_list

3.8.1.1 Description

Returns the parameters of a list of OSFs

3.8.1.2 ACLs

- osf.see-main.

3.8.1.3 Channels

- vm_created
- vm_deleted
- di_created
- di_deleted

3.8.1.4 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	
	overlay	
	user_storage	
	memory	
	vm_id	osf.filter.vm
	di_id	osf.filter.di
	creation_date	osf.filter.creation-date
	creation_admin_id	osf.filter.created-by
	creation_admin_name	osf.filter.created-by
fields <token_array>	id	
	name	
	tenant_id	
	tenant_name	
	description	osf.see.description
	overlay	osf.see.overlay
	user_storage	osf.see.user-storage
	memory	osf.see.memory
	number_of_vms	osf.see.vms-info
	number_of_dis	osf.see.dis-info
	properties	osf.see.properties
	creation_date	osf.see.creation-date
	creation_admin_id	osf.see.created-by
creation_admin_name	osf.see.created-by	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	

Parameter	Token	ACL
	description	osf.see.description
	overlay	osf.see.overlay
	user_storage	osf.see.user-storage
	memory	osf.see.memory
	creation_date	osf.see.creation-date
	creation_admin_id	osf.see.created-by
	creation_admin_name	osf.see.created-by

3.8.1.5 Examples

- Input:

```
action=osf_get_list
```

- Output:

```
{
  "rows" : [
    {
      "creation_date" : "2016-03-04T09:49:48",
      "tenant_id" : 10005,
      "name" : "OSF_Standard",
      "creation_admin_name" : "superadmin",
      "memory" : 256,
      "user_storage" : 0,
      "description" : null,
      "number_of_vms" : "1",
      "id" : 10003,
      "tenant_name" : "demo",
      "creation_admin_id" : 1,
      "properties" : {},
      "number_of_dis" : "1",
      "overlay" : 1
    },
    {
      "name" : "zOSF",
      "tenant_id" : 1,
      "creation_date" : "2016-03-03T15:19:03",
      "number_of_vms" : "2",
      "description" : null,
      "user_storage" : 0,
      "memory" : 256,
      "creation_admin_name" : "superadmin",
      "properties" : {},
      "creation_admin_id" : 1,
      "tenant_name" : "default",
      "id" : 10000,
      "overlay" : 1,
      "number_of_dis" : "1"
    }
  ],
  "message" : "Successful completion",
  "total" : 2,
  "status" : 0
}
```


3.8.2 osf_get_details

3.8.2.1 Description

Returns all the parameters of an OSF

3.8.2.2 ACLs

- osf.see-details.

3.8.2.3 Channels

- vm_created
- vm_deleted
- vm_changed
- di_created
- di_deleted

3.8.2.4 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	
fields <token_array>	id	
	name	
	tenant_id	
	tenant_name	
	description	osf.see.description
	overlay	osf.see.overlay
	user_storage	osf.see.user-storage
	memory	osf.see.memory
	number_of_vms	osf.see.vms-info
	number_of_dis	osf.see.dis-info
	properties	osf.see.properties
	creation_date	osf.see.creation-date
	creation_admin_id	osf.see.created-by
creation_admin_name	osf.see.created-by	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	osf.see.description
	overlay	osf.see.overlay
	user_storage	osf.see.user-storage
	memory	osf.see.memory
	creation_date	osf.see.creation-date
	creation_admin_id	osf.see.created-by
creation_admin_name	osf.see.created-by	

3.8.2.5 Examples

- Input:

```
action=osf_get_details&filters={"id":10000}
```

- Output:

```
{}
```

3.8.3 osf_tiny_list

3.8.3.1 Description

Returns a subset of parameters of the OSFs

3.8.3.2 ACLs

- di.create.osf
- vm.create.osf
- di.filter.osf
- vm.filter.osf

3.8.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	id	
	name	
	tenant_name	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	osf.see.description
	overlay	osf.see.overlay
	user_storage	osf.see.user-storage
	memory	osf.see.memory
	creation_date	osf.see.creation-date
	creation_admin_id	osf.see.created-by
creation_admin_name	osf.see.created-by	

3.8.3.4 Examples

- Input:

```
action=osf_tiny_list&filters={"id":10000}
```

- Output:

```
{}
```

3.8.4 osf_all_ids

3.8.4.1 Description

Returns all the ids of the OSFs

3.8.4.2 ACLs

- osf.see-main.
- osf.-massive.

3.8.4.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	
	overlay	
	user_storage	
	memory	
	vm_id	osf.filter.vm
	di_id	osf.filter.di
	creation_date	osf.filter.creation-date
	creation_admin_id	osf.filter.created-by
creation_admin_name	osf.filter.created-by	
fields <token_array>	id	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	description	osf.see.description
	overlay	osf.see.overlay
	user_storage	osf.see.user-storage
	memory	osf.see.memory
	creation_date	osf.see.creation-date
	creation_admin_id	osf.see.created-by
creation_admin_name	osf.see.created-by	

3.8.4.4 Examples

- Input:

```
action=osf_all_ids
```

- Output:

```
{}
```

3.8.5 osf_create

3.8.5.1 Description

Creates a OSF

3.8.5.2 ACLs

- osf.create.

3.8.5.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	name	
	description	
	overlay	
	user_storage	osf.create.user-storage
	memory	osf.create.memory
	tenant_id	
	__properties__	osf.create.properties

3.8.5.4 Examples

- Input:

```
action=osf_create&arguments={"name":"osf"}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "message" : "Successful completion",
  "rows" : [
    {
      "id" : 10005
    }
  ]
}
```

3.8.6 osf_update

3.8.6.1 Description

Updates the parameters of a OSF

3.8.6.2 ACLs

- osf.update.

3.8.6.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	
arguments <token_hash>	name	osf.update.name
	description	osf.update.description
	overlay	
	user_storage	osf.update.user-storage
	memory	osf.update.memory
	tenant_id	
	__properties_changes__ : set	osf.update.properties
	__properties_changes__ : delete	osf.update.properties

3.8.6.4 Examples

- Input:

```
action=osf_update&filters={"id":10000}&arguments={"memory":100}
```

- Output:

```
{
  "message" : "Successful completion",
  "rows" : [],
  "status" : 0,
  "total" : 1
}
```

3.8.7 osf_delete

3.8.7.1 Description

Deletes a OSF

3.8.7.2 ACLs

- osf.delete.

3.8.7.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	

3.8.7.4 Examples

- Input:

```
action=osf_delete&filters={"id":10000}
```

- Output:

```
{
  "rows" : [],
  "message" : "Successful completion",
  "total" : 1,
  "status" : 0
}
```

3.9 Disk Images

3.9.1 di_get_list

3.9.1.1 Description

Returns the parameters of a list of Disk Images

3.9.1.2 ACLs

- di.see-main.
- *.see.di-list

3.9.1.3 Parameters

Parameter	Token	ACL	
filters <filter_list>	id		
	disk_image		
	tenant_id		
	tenant_name		
	description		
	version		
	osf_id	di.filter.osf osf.see.di-list	
	osf_name	di.filter.osf	
	blocked		
	tag		
	creation_date		
	creation_admin_id		
	creation_admin_name		
fields <token_array>	id		
	disk_image		
	tenant_id		
	tenant_name		
	description	di.see.description	
	version	di.see.version	
	osf_id	di.see.osf	
	osf_name	di.see.osf	
	blocked	di.see.block	
	tags		di.see.tags
			di.see.head
			di.see.default
			*.see.di-list-tags
	*.see.di-list-head		

Parameter	Token	ACL
		*.see.di-list-default
	properties	di.see.properties
	creation_date	di.see.created-by
	creation_admin_id	di.see.created-by
	creation_admin_name	di.see.created-date
order_by <order_list>	id	
	disk_image	
	tenant_id	
	tenant_name	
	description	di.see.description
	version	di.see.version
	osf_id	di.see.osf
	osf_name	di.see.osf
	blocked	di.see.block
	creation_date	di.see.created-by
	creation_admin_id	di.see.created-by
	creation_admin_name	di.see.created-date

3.9.1.4 Examples

- Input:

```
action=di_get_list
```

- Output:

```
{
  "rows" : [
    {
      "creation_date" : "2016-03-04T09:50:42",
      "disk_image" : "10003-Desktop_Standard.tar.gz",
      "id" : 10003,
      "tenant_id" : 10005,
      "tenant_name" : "demo",
      "creation_admin_id" : 1,
      "osf_name" : "OSF_Standard",
      "version" : "2016-03-04-000",
      "description" : null,
      "osf_id" : 10003,
      "properties" : {},
      "creation_admin_name" : "superadmin",
      "blocked" : 0,
      "tags" : [
        {
          "fixed" : true,
          "id" : 10010,
          "tag" : "2016-03-04-000"
        },
        {
          "fixed" : false,
          "tag" : "default",
          "id" : 10012
        },
        {
          "fixed" : false,
          "tag" : "head",

```

```

        "id" : 10011
      }
    ]
  }
],
"status" : 0,
"message" : "Successful completion",
"total" : 1
}

```

3.9.2 di_get_details

3.9.2.1 Description

Returns all the parameters of a Disk Image

3.9.2.2 ACLs

- di.see-details.

3.9.2.3 Parameters

Parameter	Token	ACL	
filters <filter_list>	id		
	tenant_id		
fields <token_array>	id		
	tenant_id		
	tenant_name		
	disk_image		
	description	di.see.description	
	version	di.see.version	
	osf_id	di.see.osf	
	osf_name	di.see.osf	
	blocked	di.see.block	
	tags	di.see.tags	
		di.see.head	
		di.see.default	
		*.see.di-list-tags	
		*.see.di-list-head	
	*.see.di-list-default		
properties	di.see.properties		
creation_date	di.see.created-by		
creation_admin_id	di.see.created-by		
creation_admin_name	di.see.created-date		
order_by <order_list>	id		
	disk_image		
	tenant_id		
	tenant_name		
	description	di.see.description	
	version	di.see.version	
	osf_id	di.see.osf	
	osf_name	di.see.osf	
	blocked	di.see.block	
	creation_date	di.see.created-by	
	creation_admin_id	di.see.created-by	
	creation_admin_name	di.see.created-date	

3.9.2.4 Examples

- Input:

```
action=di_get_details&filters={"id":10003}
```

- Output:

```
{
  "status" : 0,
  "rows" : [
    {
      "disk_image" : "10003-Desktop_Standard.tar.gz",
      "creation_date" : "2016-03-04T09:50:42",
      "properties" : {},
      "osf_id" : 10003,
      "osf_name" : "OSF_Standard",
      "creation_admin_id" : 1,
      "description" : null,
      "version" : "2016-03-04-000",
      "tenant_id" : 10005,
      "id" : 10003,
      "tenant_name" : "demo",
      "tags" : [
        {
          "tag" : "2016-03-04-000",
          "id" : 10010,
          "fixed" : true
        },
        {
          "fixed" : false,
          "tag" : "default",
          "id" : 10012
        },
        {
          "tag" : "head",
          "id" : 10011,
          "fixed" : false
        }
      ],
      "blocked" : 0,
      "creation_admin_name" : "superadmin"
    }
  ],
  "total" : 1,
  "message" : "Successful completion"
}
```

3.9.3 di_all_ids

3.9.3.1 Description

Returns all the ids of the Disk Images

3.9.3.2 ACLs

- di.-massive.
- di.see-main.
- *.see.di-list

3.9.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	disk_image	di.filter.disk-image
	description	
	version	
	osf_id	di.filter.osf osf.see.di-list
	osf_name	di.filter.osf
	osf	di.filter.osf
	tenant_id	
	tenant_name	
	blocked	
	tag	
	creation_date	
	creation_admin_id	
	creation_admin_name	
fields <token_array>	id	
order_by <order_list>	id	
	tenant_id	
	tenant_name	
	disk_image	
	description	di.see.description
	version	di.see.version
	osf_id	di.see.osf
	osf_name	di.see.osf
	blocked	di.see.block
	creation_date	di.see.created-by
	creation_admin_id	di.see.created-by
	creation_admin_name	di.see.created-date

3.9.3.4 Examples

- Input:

```
action=di_all_ids
```

- Output:

```
{
  "total" : 1,
  "message" : "Successful completion",
  "status" : 0,
  "rows" : [
    10003
  ]
}
```

3.9.4 di_tiny_list

3.9.4.1 Description

Returns a subset of parameters of a list of Disk Images

3.9.4.2 ACLs

- osf.filter.di
- tenant.purge.

3.9.4.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	id	
	disk_image	
	tenant_name	
order_by <order_list>	id	
	tenant_id	
	tenant_name	
	disk_image	
	description	di.see.description
	version	di.see.version
	osf_id	di.see.osf
	osf_name	di.see.osf
	blocked	di.see.block
	creation_date	di.see.created-by
	creation_admin_id	di.see.created-by
creation_admin_name	di.see.created-date	

3.9.4.4 Examples

- Input:

```
action=di_tiny_list
```

- Output:

```
{
  "rows" : [
    {
      "tenant_name" : "demo",
      "id" : 10003,
      "disk_image" : "10003-Desktop_Standard.tar.gz"
    }
  ],
  "status" : 0,
  "message" : "Successful completion",
  "total" : 1
}
```

3.9.5 tag_get_list

3.9.5.1 Description

Returns the list of disk images tags

3.9.5.2 ACLs

- vm.create.
- vm.update.

3.9.5.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	name	
	osf_id	
	di_id	
	tenant_id	
	tenant_name	
fields <token_array>	id	
	name	
	osf_id	
	di_id	
order_by <order_list>	id	
	name	
	tenant_id	
	tenant_name	
	osf_id	
	di_id	

3.9.5.4 Examples

- Input:

```
action=tag_get_list
```

- Output:

```
{
  "status" : 0,
  "rows" : [
    {
      "osf_id" : 10003,
      "id" : 10012,
      "tenant_id" : 10005,
      "tenant_name" : "demo",
      "di_id" : 10003,
      "name" : "default"
    },
    {
      "name" : "head",
      "di_id" : 10003,
      "tenant_name" : "demo",
      "id" : 10011,
      "tenant_id" : 10005,
      "osf_id" : 10003
    },
    {
      "di_id" : 10003,
      "name" : "2016-03-04-000",
```

```

    "osf_id" : 10003,
    "tenant_id" : 10005,
    "id" : 10010,
    "tenant_name" : "demo"
  }
],
"total" : 3,
"message" : "Successful completion"
}

```

3.9.6 tag_tiny_list

3.9.6.1 Description

Returns a subset of parameters of a list of disk images tags

3.9.6.2 ACLs

- vm.create.
- vm.update.

3.9.6.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
	osf_id	
fields <token_array>	id	
	name	
order_by <order_list>	id	
	name	
	osf_id	
	di_id	

3.9.6.4 Examples

- Input:

```
action=tag_tiny_list
```

- Output:

```

{
  "status" : 0,
  "rows" : [
    {
      "id" : 10010,
      "name" : "2016-03-04-000"
    },
    {
      "id" : 10012,
      "name" : "default"
    },
    {

```

```

    "name" : "head",
    "id" : 10011
  }
],
"total" : 3,
"message" : "Successful completion"
}

```

3.9.7 di_create

3.9.7.1 Description

Creates a Disk Image

3.9.7.2 ACLs

- di.create.

3.9.7.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	disk_image	
	blocked	
	description	
	version	
	osf_id	
	__properties__	di.create.properties
	__tags__	di.create.tags
		di.create.default

3.9.7.4 Examples

- Input:

```
action=di_create
```

- Output:

```
{}
```

3.9.8 di_update

3.9.8.1 Description

Updates a Disk Image

3.9.8.2 ACLs

- di.update.

3.9.8.3 Parameters

Parameter	Token	ACL	
filters <filter_list>	id		
	tenant_id		
arguments <token_hash>	blocked	di.update.block	
	description	di.update.description	
	__properties_changes__ : set	di.update.properties	
	__properties_changes__ : delete	di.update.properties	
	__tags_changes__ : create		di.update.tags
			di.update.defaults
			osf.see.di-list-default-update
	__tags_changes__ : delete		di.update.tags
			di.update.defaults
			osf.see.di-list-default-update

3.9.8.4 Examples

- Input:

```
action=di_update
```

- Output:

```
{
  "rows" : [
    {
      "disk_image" : "10003-Desktop_Standard.tar.gz",
      "creation_date" : "2016-03-04T09:50:42",
      "osf_id" : 10003,
      "properties" : {},
      "creation_admin_id" : 1,
      "osf_name" : "OSF_Standard",
      "version" : "2016-03-04-000",
      "description" : null,
      "id" : 10003,
      "tenant_id" : 10005,
      "tenant_name" : "demo",
      "tags" : [
        {
          "tag" : "2016-03-04-000",
          "id" : 10010,
          "fixed" : true
        },
        {
          "id" : 10012,
          "tag" : "default",
          "fixed" : false
        },
        {
          "id" : 10011,
          "tag" : "head",
          "fixed" : false
        }
      ]
    },
    {
      "blocked" : 0,
      "creation_admin_name" : "superadmin"
    }
  ]
}
```

```

    }
  ],
  "status" : 0,
  "message" : "Successful completion",
  "total" : 1
}

```

3.9.9 di_delete

3.9.9.1 Description

Deletes a Disk Image

3.9.9.2 ACLs

- di.delete.

3.9.9.3 Parameters

Parameter	Token	ACL
filters	id	
<filter_list>	tenant_id	

3.9.9.4 Examples

- Input:

```
action=di_delete
```

- Output:

```
{}
```

3.9.10 dis_in_staging

3.9.10.1 Description

Returns the whole list of disk images in staging directory

3.9.10.2 ACLs

- di.create.

3.9.10.3 Parameters

Parameter	Token	ACL
-----------	-------	-----

3.9.10.4 Examples

- Input:

```
action=dis_in_staging
```

- Output:

```
{
  "message" : "Successful completion",
  "total" : 4,
  "rows" : [
    {
      "name" : "image-empty.tar.gz"
    },
    {
      "name" : "Desktop_Empty.tar.gz"
    },
    {
      "name" : "ubuntu-13.04-i386-qvd.tar.gz"
    },
    {
      "name" : "Desktop_Standard.tar.gz"
    }
  ],
  "status" : 0
}
```

3.10 Configuration

3.10.1 config_get

3.10.1.1 Description

Returns all the configuration values

3.10.1.2 ACLs

- config.qvd.
- tenant.purge.

3.10.1.3 Parameters

Parameter	Token	ACL
filters <filter_list>	key	
	tenant_id	
	operative_value	
	default_value	
	is_default	
order_by <order_list>	key	
fields <token_array>	key	
	tenant_id	
	operative_value	
	default_value	
	is_default	
info@theqvd.com	is_default	

3.10.1.4 Examples

- Input:

```
action=config_get&filters={"key":"wat"}&order_by={"order":"-desc"}
```

- Output:

```
{
  "total" : 7,
  "status" : 0,
  "rows" : [
    {
      "default_value" : null,
      "is_default" : 0,
      "key" : "wat.wat.public.fail",
      "operative_value" : "fail"
    },
    {
      "default_value" : null,
      "is_default" : 0,
      "operative_value" : "https://myqvd.theqvd.com",
      "key" : "wat.public.link"
    },
    {
      "is_default" : 0,
      "operative_value" : "1",
      "key" : "wat.multitenant",
      "default_value" : "0"
    },
    {
      "is_default" : 1,
      "key" : "wat.log.filename",
      "operative_value" : "/var/log/qvd/qvd-wat.log",
      "default_value" : "${path.log}/qvd-wat.log"
    },
    {
      "default_value" : "admin",
      "is_default" : 1,
      "key" : "wat.admin.password",
      "operative_value" : "admin"
    },
    {
      "default_value" : "admin",
      "is_default" : 1,
      "key" : "wat.admin.login",
      "operative_value" : "admin"
    },
    {
      "default_value" : "/usr/lib/qvd/wat",
      "is_default" : 1,
      "operative_value" : "/usr/lib/qvd/wat",
      "key" : "path.wat"
    }
  ],
  "message" : "Successful completion"
}
```

3.10.2 config_ssl

3.10.2.1 Description

Store SSL certificates into the configuration

3.10.2.2 ACLs

- config.qvd.

3.10.2.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	cert	
	key	
	crl	
	ca	

3.10.2.4 Examples

- Input:

```
action=config_ssl&arguments={"cert":"/path/to/cert.pem","key":"/path/to/key.pem"}
```

- Output:

```
{
  "total" : 1,
  "status" : 0,
  "rows" : [],
  "message" : "Successful completion"
}
```

3.10.3 config_set

3.10.3.1 Description

Create or update a configuration token

3.10.3.2 ACLs

- config.qvd.

3.10.3.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	tenant_id	
	key	
	value	

3.10.3.4 Examples

- Input:

```
action=config_set&arguments={"key":"admin.token","value":"token"}
```

- Output:

```
{
  "message" : "Successful completion",
  "rows" : [
    {
      "tenant_id" : 10000,
      "key" : "admin.token"
    }
  ],
  "status" : 0,
  "total" : 1
}
```

3.10.4 config_delete

3.10.4.1 Description

Deletes a configuration token

3.10.4.2 ACLs

- config.qvd.
- tenant.purge.

3.10.4.3 Parameters

Parameter	Token	ACL
filters	tenant_id	
<token_hash>	key	

3.10.4.4 Examples

- Input:

```
action=config_delete&arguments={"key":"admin.token"}
```

- Output:

```
{
  "rows" : [],
  "status" : 0,
  "message" : "Successful completion",
  "total" : 1
}
```

3.10.5 config_wat_get_details

3.10.5.1 Description

Returns the configuration of the WAT

3.10.5.2 ACLs

- config.wat.

3.10.5.3 Parameters

Parameter	Token	ACL
filters	tenant_id	
<token_hash>	block	
	language	

3.10.5.4 Examples

- Input:

```
action=config_wat_get_details
```

- Output:

```
{
  "status" : 0,
  "rows" : [
    {
      "language" : "auto",
      "block" : 10,
      "tenant_id" : 1
    }
  ],
  "message" : "Successful completion",
  "total" : 1
}
```

3.10.6 config_wat_update

3.10.6.1 Description

Updates the configuration of the WAT

3.10.6.2 ACLs

- config.wat.

3.10.6.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	tenant_id	
	block	
	language	

3.10.6.4 Examples

- Input:

```
action=config_wat_update&arguments={"block":"20"}
```

- Output:

```
{
  "status" : 0,
  "rows" : [],
  "message" : "Successful completion"
}
```

3.11 Properties

3.11.1 property_get_list

3.11.1.1 Description

Returns the parameters of a list of properties

3.11.1.2 ACLs

- property.see-main
- tenant.purge.

3.11.1.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	id	
	key	
	description	
	tenant_id	
	property_id	
	in_user	
	in_vm	
	in_host	
	in_osf	
order_by <order_list>	id	
	key	
	description	
	property_id	
	tenant_id	

3.11.1.4 Examples

- Input:

```
action=role_get_list&filters={"id":1}
```

- Output:

```
{
  "status" : 0,
  "message" : "Successful completion",
  "rows" : [
    {
      "creation_admin_id" : null,
      "acls" : {
        "positive" : [
          "administrator.create.",
          "administrator.create.language"
        ],
        "negative" : []
      },
      "tenant_id" : -1,
      "internal" : 1,
      "roles" : {},
      "name" : "Administrators Creator",
      "description" : null,
      "id" : 1,
      "creation_admin_name" : null,
      "tenant_name" : "-",
      "fixed" : 1,
      "creation_date" : null
    }
  ],
  "total" : 1
}
```

3.11.2 property_create

3.11.2.1 Description

Creates a property

3.11.2.2 ACLs

- property.see-main

3.11.2.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	key	
	tenant_id	
	description	
	__property_assign__	property.manage.

3.11.2.4 Examples

- Input:

```
action=property_create&arguments={"key":"email"}
```

- Output:

```
{
  "total" : 1,
  "rows" : [
    {
      "id" : 1
    }
  ],
  "message" : "Successful completion",
  "status" : 0
}
```

3.11.3 property_update

3.11.3.1 Description

Updates a property

3.11.3.2 ACLs

- property.see-main

3.11.3.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	
arguments <token_hash>	key	
	description	

3.11.3.4 Examples

- Input:

```
action=property_delete&filters={"id":1}&arguments={"key":"Email"}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "message" : "Successful completion",
  "rows" : []
}
```


3.11.4 property_delete

3.11.4.1 Description

Deletes a property

3.11.4.2 ACLs

- property.see-main
- tenant.purge.

3.11.4.3 Parameters

Parameter	Token	ACL
filters	id	
<filter_list>	tenant_id	

3.11.4.4 Examples

- Input:

```
action=property_delete&filters={"id":1}
```

- Output:

```
{
  "status" : 0,
  "rows" : [],
  "message" : "Successful completion",
  "total" : 1
}
```

3.11.5 host_get_property_list

3.11.5.1 Description

Returns the properties of a tenant hosts

3.11.5.2 ACLs

- host.see.properties

3.11.5.3 Parameters

Parameter	Token	ACL
filters	tenant_id	
<filter_list>		
fields	id	
<token_array>	property_id	
	key	

Parameter	Token	ACL
	description	
	tenant_id	
	tenant_name	
order_by <order_list>	id	
	key	
	property_id	

3.11.5.4 Examples

- Input:

```
action=host_get_property_list
```

- Output:

```
{
  "message" : "Successful completion",
  "rows" : [
    {
      "property_id" : 10000,
      "tenant_name" : "demo",
      "description" : null,
      "key" : "Location",
      "id" : 10002,
      "tenant_id" : 10005
    }
  ],
  "total" : 1,
  "status" : 0
}
```

3.11.6 host_create_property_list

3.11.6.1 Description

Assign a property to the hosts of a tenant

3.11.6.2 ACLs

- property.manage.host

3.11.6.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	property_id	

3.11.6.4 Examples

- Input:

```
action=host_create_property_list&arguments={"property_id":10000}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "message" : "Successful completion",
  "rows" : [
    {
      "id" : 10006
    }
  ]
}
```

3.11.7 host_delete_property_list

3.11.7.1 Description

Unassign a property from the hosts of a tenant

3.11.7.2 ACLs

- property.manage.host

3.11.7.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	

3.11.7.4 Examples

- Input:

```
action=host_delete_property_list&filters={"id":10000}
```

- Output:

```
{
  "status" : 0,
  "rows" : [],
  "message" : "Successful completion",
  "total" : 1
}
```

3.11.8 user_get_property_list

3.11.8.1 Description

Returns the properties of a tenant users

3.11.8.2 ACLs

- user.see.properties

3.11.8.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	id	
	property_id	
	key	
	description	
	tenant_id	
order_by <order_list>	tenant_name	
	id	
	key	
	property_id	

3.11.8.4 Examples

- Input:

```
action=user_get_property_list
```

- Output:

```
{
  "rows" : [
    {
      "id" : 10002,
      "key" : "Location",
      "tenant_id" : 10005,
      "property_id" : 10000,
      "tenant_name" : "demo",
      "description" : null
    }
  ],
  "message" : "Successful completion",
  "total" : 1,
  "status" : 0
}
```

3.11.9 user_create_property_list

3.11.9.1 Description

Assign a property to the users of a tenant

3.11.9.2 ACLs

- property.manage.user

3.11.9.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	property_id	

3.11.9.4 Examples

- Input:

```
action=user_create_property_list&arguments={"property_id":10001}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "message" : "Successful completion",
  "rows" : [
    {
      "id" : 10006
    }
  ]
}
```

3.11.10 user_delete_property_list

3.11.10.1 Description

Unassign a property from the users of a tenant

3.11.10.2 ACLs

- property.manage.user

3.11.10.3 Parameters

Parameter	Token	ACL
filters	id	
<filter_list>	tenant_id	

3.11.10.4 Examples

- Input:

```
action=user_delete_property_list&filters={"id":10000}
```

- Output:

```
{
  "total" : 1,
  "message" : "Successful completion",
}
```

```

    "rows" : [],
    "status" : 0
  }

```

3.11.11 vm_get_property_list

3.11.11.1 Description

Returns the properties of a tenant virtual machines

3.11.11.2 ACLs

- vm.see.properties

3.11.11.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	id	
	property_id	
	key	
	description	
	tenant_id	
	tenant_name	
order_by <order_list>	id	
	key	
	property_id	

3.11.11.4 Examples

- Input:

```
action=vm_get_property_list
```

- Output:

```

{
  "message" : "Successful completion",
  "rows" : [
    {
      "description" : null,
      "tenant_name" : "demo",
      "property_id" : 10000,
      "tenant_id" : 10005,
      "id" : 10002,
      "key" : "Location"
    }
  ],
  "total" : 1,
  "status" : 0
}

```

3.11.12 vm_create_property_list

3.11.12.1 Description

Assign a property to the virtual machines of a tenant

3.11.12.2 ACLs

- property.manage.vm

3.11.12.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	property_id	

3.11.12.4 Examples

- Input:

```
action=vm_create_property_list&arguments={"property_id":10001}
```

- Output:

```
{
  "status" : 0,
  "rows" : [
    {
      "id" : 10006
    }
  ],
  "message" : "Successful completion",
  "total" : 1
}
```

3.11.13 vm_delete_property_list

3.11.13.1 Description

Unassign a property from the virtual machines of a tenant

3.11.13.2 ACLs

- property.manage.vm

3.11.13.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	

3.11.13.4 Examples

- Input:

```
action=vm_delete_property_list&filters={"id":10000}
```

- Output:

```
{
  "status" : 0,
  "total" : 1,
  "rows" : [],
  "message" : "Successful completion"
}
```

3.11.14 osf_get_property_list

3.11.14.1 Description

Returns the properties of a tenant OSFs

3.11.14.2 ACLs

- osf.see.properties

3.11.14.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	id	
	property_id	
	key	
	description	
	tenant_id	
order_by <order_list>	tenant_name	
	id	
	key	
	property_id	

3.11.14.4 Examples

- Input:

```
action=osf_get_property_list
```

- Output:

```
{
  "message" : "Successful completion",
  "rows" : [
```



```

    {
      "description" : null,
      "property_id" : 10000,
      "tenant_name" : "demo",
      "tenant_id" : 10005,
      "key" : "Location",
      "id" : 10002
    }
  ],
  "total" : 1,
  "status" : 0
}

```

3.11.15 osf_create_property_list

3.11.15.1 Description

Assign a property to the OSFs of a tenant

3.11.15.2 ACLs

- property.manage.osf

3.11.15.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	property_id	

3.11.15.4 Examples

- Input:

```
action=osf_create_property_list&arguments={"property_id":10001}
```

- Output:

```

{
  "message" : "Successful completion",
  "rows" : [
    {
      "id" : 10006
    }
  ],
  "total" : 1,
  "status" : 0
}

```

3.11.16 osf_delete_property_list

3.11.16.1 Description

Unassign a property from the OSFs of a tenant

3.11.16.2 ACLs

- property.manage.osf

3.11.16.3 Parameters

Parameter	Token	ACL
filters <filter_list>	id	
	tenant_id	

3.11.16.4 Examples

- Input:

```
action=osf_delete_property_list&filters={"id":10000}
```

- Output:

```
{
  "message" : "Successful completion",
  "rows" : [],
  "total" : 1,
  "status" : 0
}
```

3.11.17 di_get_property_list

3.11.17.1 Description

Returns the properties of a tenant Disk Images

3.11.17.2 ACLs

- di.see.properties

3.11.17.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
fields <token_array>	id	
	property_id	
	key	
	description	
	tenant_id	
	tenant_name	
order_by <order_list>	id	
	key	
	property_id	

3.11.17.4 Examples

- Input:

```
action=di_get_property_list
```

- Output:

```
{
  "message" : "Successful completion",
  "rows" : [
    {
      "tenant_id" : 10005,
      "id" : 10002,
      "key" : "Location",
      "description" : null,
      "property_id" : 10000,
      "tenant_name" : "demo"
    }
  ],
  "total" : 1,
  "status" : 0
}
```

3.11.18 di_create_property_list

3.11.18.1 Description

Assign a property to the Disk Images of a tenant

3.11.18.2 ACLs

- property.manage.di

3.11.18.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	property_id	

3.11.18.4 Examples

- Input:

```
action=di_create_property_list&arguments={"property_id":10001}
```

- Output:

```
{
  "total" : 1,
  "message" : "Successful completion",
  "rows" : [
```

```

    {
      "id" : 10006
    }
  ],
  "status" : 0
}

```

3.11.19 di_delete_property_list

3.11.19.1 Description

Unassign a property from the Disk Images of a tenant

3.11.19.2 ACLs

- property.manage.di

3.11.19.3 Parameters

Parameter	Token	ACL
filters	id	
<filter_list>	tenant_id	

3.11.19.4 Examples

- Input:

```
action=di_delete_property_list&filters={"id":10000}
```

- Output:

```

{
  "total" : 1,
  "message" : "Successful completion",
  "rows" : [],
  "status" : 0
}

```

3.12 Views

3.12.1 tenant_view_get_list

3.12.1.1 Description

Get the list of properties and attributes to be displayed or not in each view of the WAT

3.12.1.2 ACLs

- views.update.

3.12.1.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
	field	
	visible	
	view_type	
	device_type	
	qvd_object	
	property	
fields <token_array>	tenant_id	
	field	
	visible	
	view_type	
	device_type	
	qvd_object	
	property	
order_by <order_list>	tenant_id	
	field	
	visible	
	view_type	
	device_type	
	qvd_object	
	property	

3.12.1.4 Examples

- Input:

```
action=tenant_view_get_list
```

- Output:

```
{
  "total" : 1,
  "rows" : [
    {
      "property" : 0,
      "visible" : 1,
      "field" : "creation_date",
      "view_type" : "list_column",
      "qvd_object" : "user",
      "device_type" : "desktop",
      "tenant_id" : 0
    }
  ],
  "message" : "Successful completion",
  "status" : 0
}
```

3.12.2 tenant_property_view_set

3.12.2.1 Description

Set a property to be displayed or not in a view of the WAT for a tenant

3.12.2.2 ACLs

- views.update.

3.12.2.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	qvd_obj_prop_id	
	visible	
	view_type	
	device_type	

3.12.2.4 Examples

- Input:

```
action=tenant_property_view_set&arguments={"view_type":"list_column","device_type":"desktop ←
","visible":true,"qvd_obj_prop_id":"10008"}
```

- Output:

```
{
  "status" : 0,
  "message" : "Successful completion",
  "rows" : [
    {
      "id" : 10000
    }
  ],
  "total" : 1
}
```

3.12.3 tenant_attribute_view_set

3.12.3.1 Description

Set a attribute to be displayed or not in a view of the WAT for a tenant

3.12.3.2 ACLs

- views.update.

3.12.3.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	tenant_id	
	field	
	qvd_object	
	visible	
	view_type	
	device_type	

3.12.3.4 Examples

- Input:

```
action=tenant_attribute_view_set&arguments={"view_type":"list_column","device_type":" ↵
desktop","visible":true,"qvd_object":"user","field":"id","tenant_id":"0"}
```

- Output:

```
{
  "message" : "Successful completion",
  "status" : 0,
  "total" : 1,
  "rows" : [
    {
      "id" : 10000
    }
  ]
}
```

3.12.4 tenant_view_reset

3.12.4.1 Description

Resets the columns to be displayed in view of the WAT for a tenant to default

3.12.4.2 ACLs

- config.wat.

3.12.4.3 Parameters

Parameter	Token	ACL
filters	tenant_id	
<filter_list>	qvd_object	

3.12.4.4 Examples

- Input:

```
action=tenant_attribute_view_set&arguments={"view_type":"list_column","device_type":" ↵
desktop","visible":true,"qvd_object":"user","field":"id","tenant_id":"0"}
```

- Output:

```
{
  "rows" : [],
  "status" : 0,
  "message" : "Successful completion"
}
```

3.12.5 admin_property_view_set

3.12.5.1 Description

Set a property to be displayed or not in a view of the WAT for the current administrator

3.12.5.2 ACLs

3.12.5.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	qvd_obj_prop_id	
	visible	
	view_type	
	device_type	

3.12.5.4 Examples

- Input:

```
action=admin_property_view_set&arguments={"view_type":"list_column","device_type":"desktop ←
","visible":true,"qvd_obj_prop_id":"10008"}
```

- Output:

```
{
  "total" : 1,
  "rows" : [
    {
      "id" : 10000
    }
  ],
  "message" : "Successful completion",
  "status" : 0
}
```

3.12.6 admin_attribute_view_set

3.12.6.1 Description

Set a attribute to be displayed or not in a view of the WAT for the current administrator

3.12.6.2 ACLs

3.12.6.3 Parameters

Parameter	Token	ACL
arguments <token_hash>	field	
	qvd_object	
	visible	
	view_type	
	device_type	

3.12.6.4 Examples

- Input:

```
action=admin_attribute_view_set&arguments={"view_type":"list_column","device_type":"desktop" ←
  ", "visible":true, "qvd_object":"user", "field":"id", "tenant_id":"0"}
```

- Output:

```
{
  "message" : "Successful completion",
  "status" : 0,
  "total" : 1,
  "rows" : [
    {
      "id" : 10000
    }
  ]
}
```

3.12.7 admin_view_reset

3.12.7.1 Description

Resets the columns to be displayed in view of the WAT for the current administrator to default

3.12.7.2 ACLs

3.12.7.3 Parameters

Parameter	Token	ACL
filters <filter_list>	tenant_id	
	qvd_object	

3.12.7.4 Examples

- Input:

```
action=admin_attribute_view_set&arguments={"view_type":"list_column","device_type":"desktop" ←
  ", "visible":true, "qvd_object":"user", "field":"id", "tenant_id":"0"}
```

- Output:

```
{
  "rows" : [],
  "message" : "Successful completion",
  "status" : 0
}
```

3.13 Statistics

3.13.1 qvd_objects_statistics

3.13.1.1 Description

Returns statistics about the use of QVD

3.13.1.2 ACLs

- **.stats.**

3.13.1.3 Channels

- vm_created
- vm_removed
- vm_blocked_or_unblocked
- vm_changed
- vm_expiration_date_changed
- host_created
- host_deleted
- host_blocked_or_unblocked
- host_changed
- user_created
- user_deleted
- user_blocked_or_unblocked
- user_changed
- osf_created
- osf_deleted
- osf_changed
- di_created
- di_removed
- di_blocked_or_unblocked

3.13.1.4 Parameters

Parameter	Token	ACL
-----------	-------	-----

3.13.1.5 Examples

- Input:

```
action=qvd_objects_statistics
```

- Output:

```
{
  "blocked_vms_count" : 0,
  "blocked_users_count" : 0,
  "osfs_count" : 1,
  "status" : 0,
  "running_vms_count" : 0,
  "top_populated_hosts" : [
    {
      "id" : 10000,
      "number_of_vms" : 0,
      "name" : "localhost"
    }
  ],
  "connected_users_count" : 0,
  "blocked_hosts_count" : 0,
  "blocked_dis_count" : 0,
  "hosts_count" : 1,
  "dis_count" : 1,
  "vms_count" : 1,
  "running_hosts_count" : 1,
  "vms_with_expiration_date" : [],
  "message" : "Successful completion",
  "users_count" : 1
}
```

3.14 Error Codes

A call to the API can return an error code if it has not been properly executed. The following table shows the error code and a message giving details of the reason for the same:

0	QVD_CODE_SUCCESS	Successful completion
1000	QVD_CODE_IN_PROGRESS	In progress
1100	QVD_CODE_INTERNAL_ERROR	Internal server error
1200	QVD_CODE_ACTION_INCOMPLETE	Action not accomplished for all elements
1300	QVD_CODE_ZERO_ITEMS	Zero items selected, no item has been changed
2100	QVD_CODE_DB_CONNECTION_ERROR	Connection to database
2210	QVD_CODE_STAGING_COPY_ERROR	Unable to copy disk image from staging
2211	QVD_CODE_IMAGE_COPY_ERROR	Unable to copy whole disk image (lack of space?)
2220	QVD_CODE_IMAGE_DIR_MISSING	Unable to find images directory in filesystem
2230	QVD_CODE_STAGING_DIR_MISSING	Unable to find staging directory in filesystem
2240	QVD_CODE_STAGING_FILE_MISSING	Unable to find disk image in staging directory
2250	QVD_CODE_UPLOAD_IMAGE_ERROR	Unable to upload disk image
2251	QVD_CODE_MOVE_UPLOADED_IMAGE_ERROR	Unable to move uploaded disk image
2260	QVD_CODE_DOWNLOAD_IMAGE_ERROR	Unable to download disk image
2261	QVD_CODE_MOVE_DOWNLOADED_IMAGE_ERROR	Unable to move downloaded disk image
2270	QVD_CODE_FILE_READ_ERROR	Unable to read file from disk
3100	QVD_CODE_NO_CREDENTIALS	No credentials provided for authentication
3200	QVD_CODE_WRONG_CREDENTIALS	Wrong credentials - Login again
3300	QVD_CODE_SESSION_EXPIRED	Session expired - Login again
3400	QVD_CODE_SESSION_UPDATE_ERROR	Unable to update expiration time in session
3500	QVD_CODE_TENANT_BLOCKED	Access to tenant is restricted

4100	QVD_CODE_UNAVAILABLE_ACTION	Unavailable action
4110	QVD_CODE_INVALID_ACTION	Invalid or null action name provided
4210	QVD_CODE_FORBIDDEN_ACTION	Forbidden action for this administrator
4220	QVD_CODE_FORBIDDEN_FILTER	Forbidden filter for this administrator
4221	QVD_CODE_FORBIDDEN_FILTER	Forbidden filter value for this administrator
4230	QVD_CODE_FORBIDDEN_ARGUMENT	Forbidden argument for this administrator
4240	QVD_CODE_FORBIDDEN_MASSIVE_ACTION	Massive action for this administrator
4250	QVD_CODE_FORBIDDEN_FIELD	Forbidden field for this administrator
4260	QVD_CODE_FORBIDDEN_SORT	Forbidden sort by field for this administrator
5110	QVD_CODE_DISCONNECT_USER_ERROR	Unable to disconnect user in current state
5120	QVD_CODE_STOP_VM_ERROR	Unable to stop VM in current state
5130	QVD_CODE_START_VM_ERROR	Unable to start VM in current state
5140	QVD_CODE_ASSIGN_HOST_ERROR	Unable to assign host, no host available
6100	QVD_CODE_SYNTAX_ERRORS	Syntax errors in input json
6210	QVD_CODE_INVALID_FILTER	Inappropriate filter for this action
6220	QVD_CODE_MISSING_FILTER	Mandatory filter for this action
6230	QVD_CODE_INVALID_ARGUMENT	Inappropriate argument for this action
6231	QVD_CODE_INVALID_NESTED_QUERY	Inappropriate argument for the nested query action
6240	QVD_CODE_MISSING_ARGUMENT	Mandatory argument for this action
6250	QVD_CODE_INVALID_FIELD	Inappropriate field for this action
6310	QVD_CODE_INVALID_VALUE	Invalid value
6320	QVD_CODE_INVALID_FILTER	Invalid filter value
6321	QVD_CODE_AMBIGUOUS_FILTER	Ambiguous filter value needed
6322	QVD_CODE_NON_UNIQUE_FILTER	Unique filter value needed
6330	QVD_CODE_INVALID_ARGUMENT	Invalid argument value
6340	QVD_CODE_INVALID_PROPERTY	Invalid property value
6350	QVD_CODE_INVALID_TAG	Invalid tag value
6360	QVD_CODE_INVALID_ACL	Invalid acl value
6370	QVD_CODE_INVALID_ROLE	Invalid role value
6380	QVD_CODE_INVALID_CONFIG_TOKEN	Invalid config token
6410	QVD_CODE_NON_NULLABLE_FIELD	Invalid value for a not nullable field
6420	QVD_CODE_MISSING_PROPERTY	Property value provided
6430	QVD_CODE_MISSING_TAG	No tag provided
6440	QVD_CODE_MISSING_ACL	No acl provided
6450	QVD_CODE_MISSING_ROLE	No role provided
6600	QVD_CODE_INVALID_SORT	Invalid order direction
6610	QVD_CODE_INVALID_SORT	Invalid order by field
7100	QVD_CODE_SELECT_MISSING_ITEM	Referenced items don't exist
7110	QVD_CODE_UPDATE_MISSING_ITEM	Cannot accomplish, refered related items don't exist
7120	QVD_CODE_DELETE_MISSING_ITEM	Cannot remove, other items depend on it
7200	QVD_CODE_DUPLICATED_ELEMENT	Element already exists
7210	QVD_CODE_DUPLICATED_PROPERTY	Property already exists
7220	QVD_CODE_DUPLICATED_ACL	This acl has already been assigned
7230	QVD_CODE_DUPLICATED_ROLE	This role has already been assigned
7310	QVD_CODE_DELETE_VM_ERROR	Unable to remove VM - This VM is running
7320	QVD_CODE_DELETE_DI_ERROR	Unable to remove DI - There are VMs running with it
7330	QVD_CODE_UPDATE_DI_TAG_ERROR	Unable to reassign a Tag fixed to another DI
7340	QVD_CODE_DELETE_DI_TAG_ERROR	Fixed and Default Tags cannot be deleted
7350	QVD_CODE_CYCLIC_ROLE	Forbidden role assignment, inherited role inherits from inheritor
7360	QVD_CODE_INVALID_EXPIRATION_DATE	Invalid expiration dates - Soft date must precede the hard one
7370	QVD_CODE_DELETE_CORE_CONFIG	Cannot delete a core config item
7373	QVD_CODE_SWITCH_MONOTENANT_ERROR	Cannot switch to monotenant mode - More than one tenant in the system
7382	QVD_CODE_CREATE_CONFIG_TOKEN	Cannot create new configuration token
7390	QVD_CODE_SET_DEFAULT_CONFIG	Cannot set value is already set to the default one